

# Every screen — features, functions, endpoints

132 screen groups · LOCAL images only (thumbs ≤320px / Desktop pack ≤480px). No oversized conversion. Full parameter tables live in [VERAE-API-REFERENCE.pdf](#).

| Key     | Devices                                                                            | Title                                      |
|---------|------------------------------------------------------------------------------------|--------------------------------------------|
| CERT-01 | paper:DC-01                                                                        | Certificate PDF — final (redesign)         |
| DC-01   | ios:DC-01, android:DC-A1, windows:DC-W4                                            | Sign in (unified Verae + DataCube)         |
| DC-02   | ios:DC-02, android:DC-A02, macos:DC-M02                                            | Create account — 5-step wizard             |
| DC-03   | ios:DC-03, android:DC-A03, macos:DC-M03                                            | Two-factor verification                    |
| DC-04   | ios:DC-04, android:DC-A04, macos:DC-M04                                            | Two-factor settings & enrolment            |
| DC-05   | ios:DC-05, android:DC-A2                                                           | DataCube list (home)                       |
| DC-05N  | ios:DC-05N                                                                         | New DataCube — default ops off + previous  |
| DC-06   | ios:DC-06, android:DC-A3                                                           | Cube detail — files with receipt states    |
| DC-06T  | ios:DC-06T                                                                         | File tags — on + previous selectable       |
| DC-07   | ios:DC-07                                                                          | Add file → hash → stamp                    |
| DC-07D  | ios:DC-07D, android:DC-A07D, macos:DC-M07D                                         | Add files p1 — Metadata right · Upload/Tag |
| DC-07DM | ios:DC-07DM, android:DC-A07DM, macos:DC-M07DM                                      | Add metadata per file — copy last + previo |
| DC-08   | ios:DC-08R, android:DC-A08R, macos:DC-M08R, debian:DC-L2, web:DC-B2                | Receipt restamp timeline — expandable JSON |
| DC-08R  | ios:DC-08R, android:DC-A08R, macos:DC-M08R, debian:DC-L2, web:DC-B2                | Receipt restamp timeline — expandable JSON |
| DC-09   | ios:DC-09, android:DC-A09, macos:DC-M09                                            | Cube chain — internal blocks               |
| DC-10   | ios:DC-10, android:DC-A10, macos:DC-M10                                            | Verify cube / file                         |
| DC-11   | ios:DC-11, android:DC-A5                                                           | Share & revoke (Peergos)                   |
| DC-12   | ios:DC-12, android:DC-A6                                                           | Receipts queue (waiting for final)         |
| DC-13   | ios:DC-13, android:DC-A13, windows:DC-W3, debian:DC-L3                             | Account & settings                         |
| DC-14   | ios:DC-14, android:DC-A14, macos:DC-M14                                            | Usage & billing + billing key              |
| DC-15   | ios:DC-15, debian:DC-L4                                                            | Offline & error handling                   |
| DC-16   | ios:DC-16                                                                          | Delete → tombstone confirmation            |
| DC-1    | ios:DC-01, android:DC-A1, macos:DC-M1, windows:DC-W4, debian:DC-L1, web:DC-B1      | Sign in (unified Verae + DataCube)         |
| DC-2    | ios:DC-05, android:DC-A2, macos:DC-M2, windows:DC-W2, debian:DC-L2, web:DC-B2      | DataCube list (home)                       |
| DC-3    | ios:DC-06, android:DC-A3, macos:DC-M3, windows:DC-W3, debian:DC-L3                 | Cube detail — files with receipt states    |
| DC-4    | ios:DC-08R, android:DC-A08R, macos:DC-M08R, windows:DC-W4, debian:DC-L4, web:DC-B2 | Receipt restamp timeline — expandable JSON |
| DC-5    | ios:DC-11, android:DC-A5, macos:DC-M5                                              | Share & revoke (Peergos)                   |
| DC-6    | ios:DC-12, android:DC-A6, macos:DC-M6                                              | Receipts queue (waiting for final)         |
| DC-JL1  | ios:DC-JL1                                                                         | Expandable JSONL data builder + previous t |
| DC-7    | macos:DC-M7, windows:DC-W2                                                         | Menu bar extra + notifications             |
| DC-8    | macos:DC-M8                                                                        | Offline & error states (Mac)               |
| IT-01   | android:IT-01                                                                      | Device enrollment & shift sign-in          |
| IT-02   | ios:IT-I1, android:IT-02                                                           | Field home — iOS                           |
| IT-03   | ios:IT-I2, android:IT-03                                                           | Scanner — iOS (VisionKit)                  |
| IT-04   | android:IT-04                                                                      | RFID bulk read (cage count)                |
| IT-05   | android:IT-05                                                                      | Pickup check-in (GPS GeoFix)               |
| IT-06   | android:IT-06                                                                      | Item capture — photos & identity           |
| IT-07   | android:IT-07                                                                      | Custody hand-off — QR exchange             |
| IT-08   | ios:IT-I3, android:IT-08                                                           | Signature — iOS (PencilKit)                |
| IT-09   | ios:IT-I4, android:IT-09                                                           | Grading — iOS                              |


| Key    | Devices                                  | Title                                      |
|--------|------------------------------------------|--------------------------------------------|
| IT-10  | android:IT-10                            | Floor mode — shred bin (and wipe check)    |
| IT-11  | android:IT-11                            | Offline queue                              |
| IT-12  | android:IT-12                            | Glove / outdoor (sunlight) mode            |
| IT-13  | android:IT-13                            | Lot receipts & custody timeline            |
| IT-C1  | web:IT-C1                                | Customer portal — lots                     |
| IT-C2  | web:IT-C2                                | Customer portal — lot detail               |
| IT-C3  | web:IT-C7                                | Item history — mobile web                  |
| IT-C4  | web:IT-C4                                | Certificate view + verify                  |
| IT-C5  | web:IT-C5                                | Request pickup & quote                     |
| IT-C6  | web:IT-C6                                | Settlement statements                      |
| IT-C7  | web:IT-C7                                | Item history — mobile web                  |
| IT-I1  | ios:IT-I1, android:IT-02                 | Field home — iOS                           |
| IT-I2  | ios:IT-I2, android:IT-03                 | Scanner — iOS (VisionKit)                  |
| IT-I3  | ios:IT-I3, android:IT-08                 | Signature — iOS (PencilKit)                |
| IT-I4  | ios:IT-I4, android:IT-09                 | Grading — iOS                              |
| IT-P1  | web:IT-P1                                | Partner — shared lots                      |
| IT-P2  | web:IT-P2                                | Partner — accept custody hand-off          |
| IT-P3  | web:IT-P3                                | Partner — upload evidence                  |
| IT-P4  | web:IT-P4                                | Partner — API keys & webhooks              |
| IT-S1  | windows:IT-S1                            | Station kiosk sign-in (badge + PIN)        |
| IT-S2  | windows:IT-S2                            | Dock receipt (shipment level)              |
| IT-S3  | windows:IT-S3, debian:IT-SL2             | Receiving reconciliation vs manifest       |
| IT-S4  | macos:IT-SM1, windows:IT-S4              | Supervisor approvals (Mac)                 |
| IT-S5  | windows:IT-S5, debian:IT-SL1             | Wipe station (per-drive bays)              |
| IT-S6  | windows:IT-S6                            | Shred / destruction station                |
| IT-S7  | windows:IT-S7, debian:IT-SL3             | Station offline (leaf buffering)           |
| IT-SL1 | windows:IT-S5, debian:IT-SL1             | Wipe station (per-drive bays)              |
| IT-SL2 | windows:IT-S3, debian:IT-SL2             | Receiving reconciliation vs manifest       |
| IT-SL3 | windows:IT-S7, debian:IT-SL3             | Station offline (leaf buffering)           |
| IT-SM1 | macos:IT-SM1, windows:IT-S4              | Supervisor approvals (Mac)                 |
| IT-W1  | web:IT-W1                                | Ops console — floor & dock dashboard       |
| IT-W2  | web:IT-W2                                | Lot detail — timeline & evidence           |
| IT-W3  | web:IT-W3                                | Pending-receipt queue & chain status       |
| IT-W4  | web:IT-W4                                | Pickups — schedule & assign trucks         |
| IT-W5  | web:IT-W5                                | Exceptions & cases                         |
| IT-W6  | web:IT-W6                                | Certificate lifecycle                      |
| MT-M1  | macos:MT-M1                              | Verae Timestamping (Mac) — drop, hash, rec |
| MT-M2  | macos:MT-M2                              | Export sheet with not-final guard          |
| PT-01  | macos:PT-01, windows:PT-W1, debian:PT-L1 | Print dialog → "Verae Timestamping" printe |
| PT-02  | macos:PT-02, windows:PT-W2, debian:PT-L2 | Sign-in prompt — choose how to connect     |

| Key    | Devices                                           | Title                                      |
|--------|---------------------------------------------------|--------------------------------------------|
| PT-03  | macos:PT-03                                       | Sign in · 2FA · password reset             |
| PT-04  | macos:PT-04, windows:PT-W4, debian:PT-L3          | Print job queue + receipt status           |
| PT-05  | macos:PT-05                                       | Final receipt + certificate ready          |
| PT-06  | macos:PT-06, windows:PT-W3                        | Menu bar status + notifications (Mac)      |
| PT-07  | macos:PT-07                                       | Settings (Mac)                             |
| PT-08  | macos:PT-08                                       | Offline & server-error states (printit)    |
| PT-A1  | android:PT-A1                                     | Android PrintService "Verae Timestamping"  |
| PT-B1  | web:PT-B1                                         | printit.verae.ai — download & how it works |
| PT-I1  | ios:PT-I1                                         | iOS share extension "Timestamp with Verae" |
| PT-L1  | macos:PT-01, windows:PT-W1, debian:PT-L1          | Print dialog → "Verae Timestamping" printe |
| PT-L2  | macos:PT-02, windows:PT-W2, debian:PT-L2          | Sign-in prompt — choose how to connect     |
| PT-L3  | macos:PT-04, windows:PT-W4, debian:PT-L3          | Print job queue + receipt status           |
| PT-W1  | macos:PT-01, windows:PT-W1, debian:PT-L1          | Print dialog → "Verae Timestamping" printe |
| PT-W2  | macos:PT-02, windows:PT-W2, debian:PT-L2          | Sign-in prompt — choose how to connect     |
| PT-W3  | macos:PT-06, windows:PT-W3                        | Menu bar status + notifications (Mac)      |
| PT-W4  | macos:PT-04, windows:PT-W4, debian:PT-L3          | Print job queue + receipt status           |
| SG-A1  | ios:SG-I1, android:SG-A1                          | iOS — signature request + sign             |
| SG-I1  | ios:SG-I1, android:SG-A1                          | iOS — signature request + sign             |
| SG-I2  | ios:SG-I2, macos:SG-M1, windows:SG-WN1, web:SG-W1 | iOS — send for signature (from a cube file |
| SG-L1  | debian:SG-L1, web:SG-W5                           | Debian GNOME — completion notification + S |
| SG-M1  | ios:SG-I2, macos:SG-M1, windows:SG-WN1, web:SG-W1 | iOS — send for signature (from a cube file |
| SG-P1  | paper:SG-P1                                       | Signature audit certificate (PDF)          |
| SG-W1  | ios:SG-I2, macos:SG-M1, windows:SG-WN1, web:SG-W1 | iOS — send for signature (from a cube file |
| SG-W2  | web:SG-W2                                         | Request status — step stamps               |
| SG-W3  | web:SG-W3                                         | Signer landing + email OTP                 |
| SG-W4  | web:SG-W4                                         | Sign — draw / type / upload + consent      |
| SG-W5  | debian:SG-L1, web:SG-W5                           | Debian GNOME — completion notification + S |
| SG-WN1 | ios:SG-I2, macos:SG-M1, windows:SG-WN1, web:SG-W1 | iOS — send for signature (from a cube file |
| ZP-01  | web:ZP-01                                         | Portal sign-in + 2FA                       |
| ZP-02  | web:ZP-09                                         | Portal — mobile responsive                 |
| ZP-03  | web:ZP-03                                         | Usage & metering detail                    |
| ZP-04  | web:ZP-04                                         | Invoices                                   |
| ZP-05  | web:ZP-05                                         | Statement (ledger)                         |
| ZP-06  | web:ZP-06                                         | Billing — balance, reload, cards, PO       |
| ZP-07  | web:ZP-07                                         | Security — API keys (xVerae-) & 2FA        |
| ZP-08  | web:ZP-08                                         | API & pricing                              |
| ZP-09  | web:ZP-09                                         | Portal — mobile responsive                 |
| ZP-B0  | web:ZP-B0                                         | Staff sign-in (Verae IAM)                  |
| ZP-B1  | web:ZP-B1                                         | Admin — customers                          |
| ZP-B2  | web:ZP-B2                                         | Customer support lookup                    |

| Key   | Devices     | Title                                      |
|-------|-------------|--------------------------------------------|
| ZP-B3 | web : ZP-B3 | Sales — pipeline & quotes                  |
| ZP-B4 | web : ZP-B4 | Admin — rate card & customer types         |
| ZP-B5 | web : ZP-B5 | Finance — invoices, reconciliation, period |
| ZP-B6 | web : ZP-B6 | Finance — reports                          |
| ZP-B7 | web : ZP-B7 | Compliance — audit log, evidence packs, ch |
| ZP-B8 | web : ZP-B8 | Admin — system health & users              |
| ZP-B9 | web : ZP-B9 | Staff IAM — people, roles & interface swit |
| ZP-V1 | web : ZP-V1 | Verify — entry (file, hash, QR)            |
| ZP-V2 | web : ZP-V5 | Verify — mobile (QR scan landing)          |
| ZP-V3 | web : ZP-V5 | Verify — mobile (QR scan landing)          |
| ZP-V4 | web : ZP-V4 | Verify — not found / tampered / revoked    |
| ZP-V5 | web : ZP-V5 | Verify — mobile (QR scan landing)          |

CERT-01 — Certificate PDF — final (redesign)

The printit certificate redesigned around the final-receipt rule: status box, multihash, server time, Substrate record, proof and a QR/verify link.




CERT-01

| Features                                                                                                                                      |        |                                                                        |                                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------|--------|------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Brand + certificate number + verify domain.                                                                                                 |        | • Status box: 'FINAL — Substrate block #N, finalized' with UTC and ET. |                                                                                    |
| • Fields: multihash and hex, server time (never local), VeraeTime receipt (CIDv1, not Qm...), Substrate block/extrinsic/hash, proof location. |        | • QR + human-readable verify link + 3-step how-to.                     |                                                                                    |
| • Digest-only statement and multihash definition.                                                                                             |        |                                                                        |                                                                                    |
| Function / source references                                                                                                                  |        |                                                                        |                                                                                    |
| PrintToVeraeTimeStamp/internal/pdfcert/pdfcert.go                                                                                             |        |                                                                        |                                                                                    |
| platform/registration-pdf/build.mjs                                                                                                           |        |                                                                        |                                                                                    |
| site/printit.verae.ai/samples/verae-receipt-sample.pdf                                                                                        |        |                                                                        |                                                                                    |
| API id                                                                                                                                        | Method | Path                                                                   | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                                                           | GET    | customer.verae.ai/v1/timestamp/status                                  | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                                                                                  | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                       | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                                                                                  | POST   | customer.verae.ai/v1/timestamp                                         | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-01 — Sign in (unified Verae + DataCube)

One sign-in for the Verae account (zap.verae.ai, timestamps, billing) and the Peergos DataCube account, resolving finding U-i10 (two accounts confuse users).



| DC-01                                                                                                                                                                   | DC-A1                                                                                                                                                          | DC-W4 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|
| Features                                                                                                                                                                |                                                                                                                                                                |       |
| <ul style="list-style-type: none"> <li>Brand header with the Verae mark; plain-language promise of what the account covers.</li> </ul>                                  | <ul style="list-style-type: none"> <li>Primary action is biometric when saved logins exist (Keychain on iOS; KeyStore strong biometric on Android).</li> </ul> |       |
| <ul style="list-style-type: none"> <li>Email + password fallback; password field shows focus ring (WCAG 2.4.7) and a reveal toggle with an accessible label.</li> </ul> | <ul style="list-style-type: none"> <li>Google sign-in kept from social_login.dart.</li> </ul>                                                                  |       |
| <ul style="list-style-type: none"> <li>Create account entry; Free plan copy taken from verae_first_login.dart.</li> </ul>                                               | <ul style="list-style-type: none"> <li>Advanced path for DataCube-only sign-in kept but de-emphasised.</li> </ul>                                              |       |
| <ul style="list-style-type: none"> <li>BiometricPrompt (BIOMETRIC_STRONG, KeyStore-backed); declare USE_BIOMETRIC (U-a2 verify).</li> </ul>                             | <ul style="list-style-type: none"> <li>Outlined text fields with floating labels (M3).</li> </ul>                                                              |       |
| <ul style="list-style-type: none"> <li>Credential Manager for Google / passkeys.</li> </ul>                                                                             | <ul style="list-style-type: none"> <li>ContentDialog with primary/close buttons in footer; Enter/Esc.</li> </ul>                                               |       |


| Function / source references                              |
|-----------------------------------------------------------|
| lib/main.dart LoginScreen                                 |
| lib/auth/verae_first_login.dart VeraeLoginScreen          |
| auth/biometric_login.dart                                 |
| auth/social_login.dart                                    |
| auth/saved_logins.dart                                    |
| lib/main.dart                                             |
| lib/auth/biometric_login.dart (KeyStore strong biometric) |
| lib/auth/verae_first_login.dart                           |
| lib/auth/biometric_login.dart                             |

| API id              | Method          | Path                                             | Key params (name:type)                                                                                                             |
|---------------------|-----------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| v1.timestamp.status | GET             | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                                              |
| peergos.cube        | —               | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests       | POST            | sign.verae.ai/sign/v1/requests                   | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp        | POST            | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |
| portal.usage        | GET             | customer.verae.ai/portal/api/usage               | peergosUsername:string?, from,to:ISO date?                                                                                         |
| portal.tokens       | GET/POST/DELETE | customer.verae.ai/portal/api/tokens              | name:string, id:string                                                                                                             |
| portal.login        | POST            | customer.verae.ai/portal/api/login               | email:string, password:string, totpCode:string (6 digits)                                                                          |
| portal.billing      | GET/POST        | customer.verae.ai/portal/api/billing/*           | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                                    |
| portal.profile      | GET/PATCH       | customer.verae.ai/portal/api/profile             | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164      |
| sign.public.sign    | POST            | sign.verae.ai/sign/v1/public/:token/sign         | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-02 — Create account — 5-step wizard

Sign-up that creates the Verae account and the DataCube (Peergos) account together, with free movement between steps.




| DC-02                                                                                       |                 | DC-A02                                           |                                                     | DC-M02                                                                     |  |
|---------------------------------------------------------------------------------------------|-----------------|--------------------------------------------------|-----------------------------------------------------|----------------------------------------------------------------------------|--|
| Features                                                                                    |                 |                                                  |                                                     |                                                                            |  |
| • Stepper with named steps; steps are tappable to move freely (commit 32c7011).             |                 |                                                  | • Password with focus ring and reveal.              |                                                                            |  |
| • Strength meter uses text + icon, never colour alone (WCAG 1.4.1).                         |                 |                                                  | • Generate password (auth/generated_password.dart). |                                                                            |  |
| • Unrecoverable-data warning copied from verae_first_login.dart, given a warning container. |                 |                                                  | • Same-password choice (commits 35d2342, 3c9774e).  |                                                                            |  |
| • Linear 5-step progress.                                                                   |                 |                                                  | • Password fields + strength text+icon.             |                                                                            |  |
| • Generate password.                                                                        |                 |                                                  | • Unrecoverable-data warning.                       |                                                                            |  |
| • Same vs different DataCube password.                                                      |                 |                                                  | • 5-step bar.                                       |                                                                            |  |
| Function / source references                                                                |                 |                                                  |                                                     |                                                                            |  |
| lib/signup_screen.dart CreateAccountScreen, VeraeAccountStep                                |                 |                                                  |                                                     |                                                                            |  |
| lib/auth/veraefirstlogin.dart (Step n of 5)                                                 |                 |                                                  |                                                     |                                                                            |  |
| lib/signup_rules.dart                                                                       |                 |                                                  |                                                     |                                                                            |  |
| lib/datacube/datacube_ui.dart                                                               |                 |                                                  |                                                     |                                                                            |  |
| lib/auth/*                                                                                  |                 |                                                  |                                                     |                                                                            |  |
| lib/billing/*                                                                               |                 |                                                  |                                                     |                                                                            |  |
| lib/signup_screen.dart                                                                      |                 |                                                  |                                                     |                                                                            |  |
| API id                                                                                      | Method          | Path                                             |                                                     | Key params (name:type)                                                     |  |
| portal.signup                                                                               | POST            | customer.verae.ai/portal/api/signup              |                                                     | name:string, email:string (email), password:string (≥8), acceptTos:boolean |  |
| peergos.cube                                                                                | —               | peergos.verae.ai (Peergos HTTP/API + local rust) |                                                     | username:string, password:string, path:string, bytes:bytes                 |  |
| portal.tokens                                                                               | GET/POST/DELETE | customer.verae.ai/portal/api/tokens              |                                                     | name:string, id:string                                                     |  |

Sample calls + full param tables → [VERAE-API-REFERENCE.pdf](#)

DC-03 — Two-factor verification

Single TOTP step shared by Verae and DataCube sign-in (today TOTP appears in two places: main sign-in and the timestamps portal dialog).




| Features                                                                         |                 |                                                            |                                                                                    |
|----------------------------------------------------------------------------------|-----------------|------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Six segmented digit boxes; one-time-code content type so AutoFill can fill it. |                 | • AutoFill hint.                                           |                                                                                    |
| • Verify; auto-submits on the 6th digit.                                         |                 | • Backup codes path (two_factor_screen.dart backup-codes). |                                                                                    |
| • Explains a single code covers both accounts.                                   |                 | • Six digit cells + autofill.                              |                                                                                    |
| • Verify + backup code.                                                          |                 | • Both-accounts banner.                                    |                                                                                    |
| • TOTP digits.                                                                   |                 | • Backup + Verify.                                         |                                                                                    |
| • Both-accounts note.                                                            |                 |                                                            |                                                                                    |
| Function / source references                                                     |                 |                                                            |                                                                                    |
| lib/auth/two_factor_screen.dart                                                  |                 |                                                            |                                                                                    |
| lib/timestamps/timestamps_ui.dart _VtLoginDialog (TOTP)                          |                 |                                                            |                                                                                    |
| lib/auth/verae_first_login.dart                                                  |                 |                                                            |                                                                                    |
| lib/datacube/datacube_ui.dart                                                    |                 |                                                            |                                                                                    |
| lib/auth/*                                                                       |                 |                                                            |                                                                                    |
| lib/billing/*                                                                    |                 |                                                            |                                                                                    |
| lib/signup_screen.dart                                                           |                 |                                                            |                                                                                    |
| API id                                                                           | Method          | Path                                                       | Key params (name:type)                                                             |
| v1.timestamp.status                                                              | GET             | customer.verae.ai/v1/timestamp/status                      | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                     | —               | peergos.verae.ai (Peergos HTTP/API + local rust)           | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                     | POST            | customer.verae.ai/v1/timestamp                             | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |
| portal.login                                                                     | POST            | customer.verae.ai/portal/api/login                         | email:string, password:string, totpCode:string (6 digits)                          |
| portal.2fa                                                                       | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*                         | setup:POST {}, code:string, totpCode:string                                        |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

DC-04 — Two-factor settings & enrolment

Manage authenticator, backup codes and biometric unlock; enrol a new authenticator with QR + manual secret.



DC-04

DC-A04

DC-M04

| Features                                                                                  |                 |                                              |                                                           |
|-------------------------------------------------------------------------------------------|-----------------|----------------------------------------------|-----------------------------------------------------------|
| • QR to otpauth:// URI (issuer Verae); VoiceOver label 'QR code for authenticator setup'. |                 | • Manual secret, grouped in 4s, copy button. |                                                           |
| • Turn on is enabled after a valid code.                                                  |                 | • WebAuthn note from current code.           |                                                           |
| • Methods list.                                                                           |                 | • QR + secret + turn on.                     |                                                           |
| • Portal note for passkeys.                                                               |                 | • Portal note.                               |                                                           |
| Function / source references                                                              |                 |                                              |                                                           |
| lib/auth/two_factor_screen.dart (_EnrollDialog, backup codes)                             |                 |                                              |                                                           |
| lib/auth/authenticator_setup.dart                                                         |                 |                                              |                                                           |
| lib/datacube/datacube_ui.dart                                                             |                 |                                              |                                                           |
| lib/auth/*                                                                                |                 |                                              |                                                           |
| lib/billing/*                                                                             |                 |                                              |                                                           |
| lib/signup_screen.dart                                                                    |                 |                                              |                                                           |
| API id                                                                                    | Method          | Path                                         | Key params (name:type)                                    |
| portal.login                                                                              | POST            | customer.verae.ai/portal/api/login           | email:string, password:string, totpCode:string (6 digits) |
| portal.2fa                                                                                | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*           | setup:POST {}, code:string, totpCode:string               |

Sample calls + full param tables → [VERAE-API-REFERENCE.pdf](#)

DC-05 — DataCube list (home)

Home screen: all cubes with an at-a-glance evidence status per cube and a global 'receipts waiting' indicator.



DC-05


DC-A2

| Features                                                                                                         |        |                                                  |                                                                                    |
|------------------------------------------------------------------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Global pending banner (U-i3): count of not-final receipts with a jump to the Receipts queue.                   |        | • Filter chips incl. 'Attention'.                |                                                                                    |
| • Cube rows: cube glyph, size, chain health, status badge with text (never colour only).                         |        | • Sync + storage line (billing context).         |                                                                                    |
| • Tonal warning card for pending receipts.                                                                       |        | • M3 filter chips with check icon when selected. |                                                                                    |
| • Extended FAB 'New DataCube' (collapses on scroll); navigation bar with 5 destinations; predictive back (U-a3). |        |                                                  |                                                                                    |
| Function / source references                                                                                     |        |                                                  |                                                                                    |
| lib/datacube/datacube_ui.dart CubeListScreen, DataCubesEdgeTab (empty text 'No DataCubes yet.')                  |        |                                                  |                                                                                    |
| lib/datacube/datacube_ui.dart CubeListScreen                                                                     |        |                                                  |                                                                                    |
| file_browser.dart bottom bar                                                                                     |        |                                                  |                                                                                    |
| API id                                                                                                           | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                              | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                                                     | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                                                     | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-05N — New DataCube — default ops off + previous tags

Create cube; default Upload/Tags/Timestamp icon toggles start off; previous tags library.



DC-05N

| Features                       |                 |                                                  |                                                                                                                     |
|--------------------------------|-----------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Name.                        |                 | • Three ops off.                                 |                                                                                                                     |
| • Previous tags.               |                 | • Create.                                        |                                                                                                                     |
| Function / source references   |                 |                                                  |                                                                                                                     |
| lib/files/*                    |                 |                                                  |                                                                                                                     |
| lib/datacube/*                 |                 |                                                  |                                                                                                                     |
| lib/timestamps/*               |                 |                                                  |                                                                                                                     |
| peergos                        |                 |                                                  |                                                                                                                     |
| customer.verae.ai/v1/timestamp |                 |                                                  |                                                                                                                     |
| API id                         | Method          | Path                                             | Key params (name:type)                                                                                              |
| v1.timestamp.status            | GET             | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                               |
| peergos.cube                   | —               | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                   | POST            | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |
| portal.signup                  | POST            | customer.verae.ai/portal/api/signup              | name:string, email:string (email), password:string (≥8), acceptTos:boolean                                          |
| portal.tokens                  | GET/POST/DELETE | customer.verae.ai/portal/api/tokens              | name:string, id:string                                                                                              |
| add.destination                | local + APIs    | App add flow (DC-07D)                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |

Sample calls + full param tables → VERA-E-API-REFERENCE.pdf

DC-06 — Cube detail — files with receipt states

Shows a cube's files, each with its receipt state per George's rule, plus tombstoned (deleted) entries kept in history.




| DC-06                                                                                                    |              | DC-A3                                                                                                                                                                                     |                                                                                                                     |
|----------------------------------------------------------------------------------------------------------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Features                                                                                                 |              |                                                                                                                                                                                           |                                                                                                                     |
| • Cube header: owner, block count, chain verification time, share count.                                 |              | • Primary cube actions: Chain (DC-09), Verify (DC-10), Share (DC-11).                                                                                                                     |                                                                                                                     |
| • 'Show deleted' toggle (CheckedPopupMenuItem 'Show deleted' today).                                     |              | • File rows: name, size, short multihash, receipt badge: Final · #N / #N · not final / Pending receipt / Existing / Queued offline. Tombstones struck through with 'Deleted in block 54'. |                                                                                                                     |
| • Add file → DC-07 (Files, Photos, Camera, Scan).                                                        |              | • Same receipt badges as iOS (shared component).                                                                                                                                          |                                                                                                                     |
| • M3 modal bottom sheet replaces the iOS action sheet.                                                   |              | • WorkManager for queued uploads and receipt reconcile (U-a5) with a foreground progress notification.                                                                                    |                                                                                                                     |
| Function / source references                                                                             |              |                                                                                                                                                                                           |                                                                                                                     |
| lib/datacube/datacube_ui.dart CubeScreen (tombstoned rows, 'Show deleted', 'Timestamp un-stamped files') |              |                                                                                                                                                                                           |                                                                                                                     |
| lib/datacube/datacube_ui.dart CubeScreen                                                                 |              |                                                                                                                                                                                           |                                                                                                                     |
| files/sync_queue.dart                                                                                    |              |                                                                                                                                                                                           |                                                                                                                     |
| lib/files/file_browser.dart                                                                              |              |                                                                                                                                                                                           |                                                                                                                     |
| lib/timestamps/auto_stamp.dart                                                                           |              |                                                                                                                                                                                           |                                                                                                                     |
| API id                                                                                                   | Method       | Path                                                                                                                                                                                      | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                                                      | GET          | customer.verae.ai/v1/timestamp/status                                                                                                                                                     | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                                                          | local + APIs | App add flow (DC-07D)                                                                                                                                                                     | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                                                             | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                                                                                                                                          | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                                             | POST         | customer.verae.ai/v1/timestamp                                                                                                                                                            | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-06T — File tags — on + previous selectable

Edit tags; previous tags unselected until tapped; optional restamp default off.




DC-06T

| Features                       |              |                                                  |                                                                                                                     |
|--------------------------------|--------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • On tags.                     |              | • Previous tags.                                 |                                                                                                                     |
| • Restamp toggle off.          |              | • Save.                                          |                                                                                                                     |
| Function / source references   |              |                                                  |                                                                                                                     |
| lib/files/*                    |              |                                                  |                                                                                                                     |
| lib/datacube/*                 |              |                                                  |                                                                                                                     |
| lib/timestamps/*               |              |                                                  |                                                                                                                     |
| peergos                        |              |                                                  |                                                                                                                     |
| customer.verae.ai/v1/timestamp |              |                                                  |                                                                                                                     |
| lib/files/file_browser.dart    |              |                                                  |                                                                                                                     |
| lib/timestamps/auto_stamp.dart |              |                                                  |                                                                                                                     |
| API id                         | Method       | Path                                             | Key params (name:type)                                                                                              |
| v1.timestamp.status            | GET          | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                | local + APIs | App add flow (DC-07D)                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                   | —            | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                   | POST         | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-07 — Add file → hash → stamp

Adds files to a cube: hashes on device, checks if already registered (instant existing receipt), stamps new hashes, encrypts and stores in the cube.




DC-07

| Features                                                                            |              |                                                                                                                                  |                                                                                                                     |
|-------------------------------------------------------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Verae timestamp registry (hash only)                                              |              | • Expandable nested JSONL builder + path diffs                                                                                   |                                                                                                                     |
| • Copy last metadata per item                                                       |              | • Previous tags unselected — tap to turn on                                                                                      |                                                                                                                     |
| • Upload / Tags / Timestamp: separate icon toggles, DEFAULT OFF                     |              | • Metadata button on the RIGHT of each file row                                                                                  |                                                                                                                     |
| • Per-file card: hashing progress → multihash → 'Pending receipt'.                  |              | • Duplicate path: hash already registered → 'Already registered' badge and the existing final receipt immediately (doc 21 rule). |                                                                                                                     |
| • Large-file hashing in the Rust core, with progress; cancel per file.              |              | • Stamp and encrypt toggles; stamping is on by default and always goes to Substrate.                                             |                                                                                                                     |
| • Multihash rule stated plainly.                                                    |              |                                                                                                                                  |                                                                                                                     |
| Function / source references                                                        |              |                                                                                                                                  |                                                                                                                     |
| lib/datacube/datacube_ui.dart (Add files / photos dialogs, 'Adding to DataCube...') |              |                                                                                                                                  |                                                                                                                     |
| lib/files/file_browser.dart (image_picker camera)                                   |              |                                                                                                                                  |                                                                                                                     |
| lib/timestamps/auto_stamp.dart                                                      |              |                                                                                                                                  |                                                                                                                     |
| lib/files/file_browser.dart                                                         |              |                                                                                                                                  |                                                                                                                     |
| API id                                                                              | Method       | Path                                                                                                                             | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                                 | GET          | customer.verae.ai/v1/timestamp/status                                                                                            | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                                     | local + APIs | App add flow (DC-07D)                                                                                                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                                        | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                                                                                 | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                        | POST         | customer.verae.ai/v1/timestamp                                                                                                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-07D — Add files p1 — Metadata right · Upload/Tags/Timestamp off

Page 1 Adding to Contracts: per-file Metadata button on the right; Upload, Tags, Timestamp as separate icon toggles default off. Metadata sheet: copy last metadata, previous tags selectable, JSONL bui




| DC-07D                                                          |              | DC-A07D                                          |                                                                    | DC-M07D                                                                                                             |  |
|-----------------------------------------------------------------|--------------|--------------------------------------------------|--------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|--|
| Features                                                        |              |                                                  |                                                                    |                                                                                                                     |  |
| • Verae timestamp registry (hash only)                          |              |                                                  | • Expandable nested JSONL builder + path diffs                     |                                                                                                                     |  |
| • Copy last metadata per item                                   |              |                                                  | • Previous tags unselected — tap to turn on                        |                                                                                                                     |  |
| • Upload / Tags / Timestamp: separate icon toggles, DEFAULT OFF |              |                                                  | • Metadata button on the RIGHT of each file row                    |                                                                                                                     |  |
| • File rows with Metadata button on the right.                  |              |                                                  | • Upload / Tags / Timestamp icon toggles — default Off (unpushed). |                                                                                                                     |  |
| • Upload ≠ Tags ≠ Timestamp.                                    |              |                                                  | • Continue / Cancel.                                               |                                                                                                                     |  |
| • Metadata right.                                               |              |                                                  | • Upload/Tags/Timestamp off.                                       |                                                                                                                     |  |
| Function / source references                                    |              |                                                  |                                                                    |                                                                                                                     |  |
| lib/files/*                                                     |              |                                                  |                                                                    |                                                                                                                     |  |
| lib/datacube/*                                                  |              |                                                  |                                                                    |                                                                                                                     |  |
| lib/timestamps/*                                                |              |                                                  |                                                                    |                                                                                                                     |  |
| peergos                                                         |              |                                                  |                                                                    |                                                                                                                     |  |
| customer.verae.ai/v1/timestamp                                  |              |                                                  |                                                                    |                                                                                                                     |  |
| lib/files/file_browser.dart                                     |              |                                                  |                                                                    |                                                                                                                     |  |
| lib/timestamps/auto_stamp.dart                                  |              |                                                  |                                                                    |                                                                                                                     |  |
| API id                                                          | Method       | Path                                             |                                                                    | Key params (name:type)                                                                                              |  |
| v1.timestamp.status                                             | GET          | customer.verae.ai/v1/timestamp/status            |                                                                    | sha256:string (64 hex), jobld:string?                                                                               |  |
| add.destination                                                 | local + APIs | App add flow (DC-07D)                            |                                                                    | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |  |
| peergos.cube                                                    | —            | peergos.verae.ai (Peergos HTTP/API + local rust) |                                                                    | username:string, password:string, path:string, bytes:bytes                                                          |  |
| v1.timestamp                                                    | POST         | customer.verae.ai/v1/timestamp                   |                                                                    | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                  |  |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

DC-07DM — Add metadata per file — copy last + previous tags

Per-item metadata: Copy last metadata; tags on + previous unselected tags to turn on; expandable JSONL builder.




| DC-07DM                                                         |              | DC-A07DM                                         |  | DC-M07DM                                                                                                            |  |
|-----------------------------------------------------------------|--------------|--------------------------------------------------|--|---------------------------------------------------------------------------------------------------------------------|--|
| Features                                                        |              |                                                  |  |                                                                                                                     |  |
| • Verae timestamp registry (hash only)                          |              | • Expandable nested JSONL builder + path diffs   |  |                                                                                                                     |  |
| • Copy last metadata per item                                   |              | • Previous tags unselected — tap to turn on      |  |                                                                                                                     |  |
| • Upload / Tags / Timestamp: separate icon toggles, DEFAULT OFF |              | • Metadata button on the RIGHT of each file row  |  |                                                                                                                     |  |
| • Copy last metadata.                                           |              | • Tags on + previous tags (tap to select).       |  |                                                                                                                     |  |
| • JSONL nested builder + diff history.                          |              | • Save metadata.                                 |  |                                                                                                                     |  |
| • Copy last.                                                    |              | • Previous tags.                                 |  |                                                                                                                     |  |
| Function / source references                                    |              |                                                  |  |                                                                                                                     |  |
| lib/files/*                                                     |              |                                                  |  |                                                                                                                     |  |
| lib/datacube/*                                                  |              |                                                  |  |                                                                                                                     |  |
| lib/timestamps/*                                                |              |                                                  |  |                                                                                                                     |  |
| peergos                                                         |              |                                                  |  |                                                                                                                     |  |
| customer.verae.ai/v1/timestamp                                  |              |                                                  |  |                                                                                                                     |  |
| lib/files/file_browser.dart                                     |              |                                                  |  |                                                                                                                     |  |
| lib/timestamps/auto_stamp.dart                                  |              |                                                  |  |                                                                                                                     |  |
| API id                                                          | Method       | Path                                             |  | Key params (name:type)                                                                                              |  |
| v1.timestamp.status                                             | GET          | customer.verae.ai/v1/timestamp/status            |  | sha256:string (64 hex), jobId:string?                                                                               |  |
| add.destination                                                 | local + APIs | App add flow (DC-07D)                            |  | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |  |
| peergos.cube                                                    | —            | peergos.verae.ai (Peergos HTTP/API + local rust) |  | username:string, password:string, path:string, bytes:bytes                                                          |  |
| v1.timestamp                                                    | POST         | customer.verae.ai/v1/timestamp                   |  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-08 — Receipt restamp timeline — expandable JSONL + diffs


Shows a file's original timestamp receipt and each restamp with additional JSONL payloads. Entries expand to nested JSON and per-field diff history.



DC-08R

DC-A08R

DC-M08R



DC-L2


DC-B2

| Features                                                                        |              |                                                             |                                                                                                                     |
|---------------------------------------------------------------------------------|--------------|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Header: file, sha256, restamp count.                                          |              | • Timeline newest-first; expand/collapse.                   |                                                                                                                     |
| • Expanded: pretty JSONL nested object + diff history list (path, op, from/to). |              | • restampOf link to parent job.                             |                                                                                                                     |
| • Original receipt footer (no additional data).                                 |              | • Contract note: restamp:true; digests of additional JSONL. |                                                                                                                     |
| • M3 top app bar.                                                               |              | • Expandable cards.                                         |                                                                                                                     |
| • JSONL + diff list.                                                            |              | • Original footer.                                          |                                                                                                                     |
| • Split: timeline   detail.                                                     |              | • JSONL pretty + diff table.                                |                                                                                                                     |
| Function / source references                                                    |              |                                                             |                                                                                                                     |
| lib/timestamps/*                                                                |              |                                                             |                                                                                                                     |
| CORE-CONTRACT restampOf                                                         |              |                                                             |                                                                                                                     |
| archive JSONL additional                                                        |              |                                                             |                                                                                                                     |
| lib/timestamps/timestamps_ui.dart                                               |              |                                                             |                                                                                                                     |
| New                                                                             |              |                                                             |                                                                                                                     |
| API id                                                                          | Method       | Path                                                        | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                             | GET          | customer.verae.ai/v1/timestamp/status                       | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                                 | local + APIs | App add flow (DC-07D)                                       | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                                    | —            | peergos.verae.ai (Peergos HTTP/API + local rust)            | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                    | POST         | customer.verae.ai/v1/timestamp                              | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERA-API-REFERENCE.pdf

DC-08R — Receipt restamp timeline — expandable JSONL + diffs


Shows a file's original timestamp receipt and each restamp with additional JSONL payloads. Entries expand to nested JSON and per-field diff history.



DC-08R

DC-A08R

DC-M08R



DC-L2


DC-B2

| Features                                                                        |              |                                                             |                                                                                                                     |
|---------------------------------------------------------------------------------|--------------|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Header: file, sha256, restamp count.                                          |              | • Timeline newest-first; expand/collapse.                   |                                                                                                                     |
| • Expanded: pretty JSONL nested object + diff history list (path, op, from/to). |              | • restampOf link to parent job.                             |                                                                                                                     |
| • Original receipt footer (no additional data).                                 |              | • Contract note: restamp:true; digests of additional JSONL. |                                                                                                                     |
| • M3 top app bar.                                                               |              | • Expandable cards.                                         |                                                                                                                     |
| • JSONL + diff list.                                                            |              | • Original footer.                                          |                                                                                                                     |
| • Split: timeline   detail.                                                     |              | • JSONL pretty + diff table.                                |                                                                                                                     |
| Function / source references                                                    |              |                                                             |                                                                                                                     |
| lib/timestamps/*                                                                |              |                                                             |                                                                                                                     |
| CORE-CONTRACT restampOf                                                         |              |                                                             |                                                                                                                     |
| archive JSONL additional                                                        |              |                                                             |                                                                                                                     |
| lib/timestamps/timestamps_ui.dart                                               |              |                                                             |                                                                                                                     |
| New                                                                             |              |                                                             |                                                                                                                     |
| API id                                                                          | Method       | Path                                                        | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                             | GET          | customer.verae.ai/v1/timestamp/status                       | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                                 | local + APIs | App add flow (DC-07D)                                       | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                                    | —            | peergos.verae.ai (Peergos HTTP/API + local rust)            | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                    | POST         | customer.verae.ai/v1/timestamp                              | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERA-REFERENCE.pdf

DC-09 — Cube chain — internal blocks

Visualises the cube's internal hash chain: adds, shares, revokes and tombstones as blocks, each with its own Substrate registration state.



DC-09

DC-A09


DC-M09

| Features                                                                                                 |              |                                                                                                                                                                               |                                                                                                                     |
|----------------------------------------------------------------------------------------------------------|--------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Chain summary + head hash; explains linkage in one sentence.                                           |              | • Block cards: sequence, event (add / share / revoke / tombstone), prev → this hash, per-block receipt state. Tombstone blocks are red-tinted; deletes never rewrite history. |                                                                                                                     |
| • Summary + head hash.                                                                                   |              | • Block cards with event type and receipt stage.                                                                                                                              |                                                                                                                     |
| • Summary.                                                                                               |              | • Table seq/event/prev/hash/receipt.                                                                                                                                          |                                                                                                                     |
| • Verify → DC-M10.                                                                                       |              |                                                                                                                                                                               |                                                                                                                     |
| Function / source references                                                                             |              |                                                                                                                                                                               |                                                                                                                     |
| lib/datacube/datacube_ui.dart CubeChainScreen ('Chain (all blocks)', seq · blockId · createdAt · sha256) |              |                                                                                                                                                                               |                                                                                                                     |
| lib/datacube/datacube_ui.dart                                                                            |              |                                                                                                                                                                               |                                                                                                                     |
| lib/auth/*                                                                                               |              |                                                                                                                                                                               |                                                                                                                     |
| lib/billing/*                                                                                            |              |                                                                                                                                                                               |                                                                                                                     |
| lib/signup_screen.dart                                                                                   |              |                                                                                                                                                                               |                                                                                                                     |
| CubeChainScreen                                                                                          |              |                                                                                                                                                                               |                                                                                                                     |
| API id                                                                                                   | Method       | Path                                                                                                                                                                          | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                                                      | GET          | customer.verae.ai/v1/timestamp/status                                                                                                                                         | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                                                          | local + APIs | App add flow (DC-07D)                                                                                                                                                         | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                                                             | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                                                                                                                              | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                                             | POST         | customer.verae.ai/v1/timestamp                                                                                                                                                | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-10 — Verify cube / file

Re-hashes all blocks and files locally and checks Substrate registrations; reports success, not-final items and tampering.



| DC-10                                                                                             |        | DC-A10                                                                        |  | DC-M10                                                     |  |
|---------------------------------------------------------------------------------------------------|--------|-------------------------------------------------------------------------------|--|------------------------------------------------------------|--|
| Features                                                                                          |        |                                                                               |  |                                                            |  |
| • Result hero with icon + words (not colour only).                                                |        | • Check list: chain links, file contents, Substrate registration, tombstones. |  |                                                            |  |
| • Not-final caveat banner.                                                                        |        | • Exportable verification report (itself stamped).                            |  |                                                            |  |
| • Result hero.                                                                                    |        | • Check list.                                                                 |  |                                                            |  |
| • Not-final banner.                                                                               |        | • Export + single-file verify.                                                |  |                                                            |  |
| • Export + Done.                                                                                  |        |                                                                               |  |                                                            |  |
| Function / source references                                                                      |        |                                                                               |  |                                                            |  |
| lib/datacube/datacube_ui.dart CubeVerifyScreen ('Verify chain', 'Re-hashing blocks and files...') |        |                                                                               |  |                                                            |  |
| lib/src/rust/api/datacube.dart                                                                    |        |                                                                               |  |                                                            |  |
| lib/datacube/datacube_ui.dart                                                                     |        |                                                                               |  |                                                            |  |
| lib/auth/*                                                                                        |        |                                                                               |  |                                                            |  |
| lib/billing/*                                                                                     |        |                                                                               |  |                                                            |  |
| lib/signup_screen.dart                                                                            |        |                                                                               |  |                                                            |  |
| CubeVerifyScreen                                                                                  |        |                                                                               |  |                                                            |  |
| API id                                                                                            | Method | Path                                                                          |  | Key params (name:type)                                     |  |
| portal.login                                                                                      | POST   | customer.verae.ai/portal/api/login                                            |  | email:string, password:string, totpCode:string (6 digits)  |  |
| v1.timestamp.status                                                                               | GET    | customer.verae.ai/v1/timestamp/status                                         |  | sha256:string (64 hex), jobId:string?                      |  |
| peergos.cube                                                                                      | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                              |  | username:string, password:string, path:string, bytes:bytes |  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## DC-11 — Share & revoke (Peergos)

Share a cube or file with Peergos users/groups or a link; revoke access. Shares and revokes are cube-chain blocks with their own timestamps.



| DC-11                                                                                        |        | DC-A5                                                                |                                                                                    |
|----------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                                     |        |                                                                      |                                                                                    |
| • Chain-recording explanation (existing copy, elevated).                                     |        | • Invite by Peergos username/email with view/edit segmented control. |                                                                                    |
| • Access list with Remove (destructive style + confirmation).                                |        | • Links with expiry and Revoke.                                      |                                                                                    |
| • Channels: new link, SMS (existing 'Send by text'), iOS share sheet.                        |        | • Full-screen dialog pattern on compact width (M3).                  |                                                                                    |
| • Android sharesheet with direct-share targets; revoke uses an M3 dialog (same copy as iOS). |        |                                                                      |                                                                                    |
| Function / source references                                                                 |        |                                                                      |                                                                                    |
| lib/sharing/sharing_ui.dart ShareScreen, _NewLinkDialog, PeopleScreen, LinksScreen           |        |                                                                      |                                                                                    |
| lib/src/rust/api/sharing.dart revokeAccess                                                   |        |                                                                      |                                                                                    |
| lib/sharing/sharing_ui.dart (share sheet)                                                    |        |                                                                      |                                                                                    |
| API id                                                                                       | Method | Path                                                                 | Key params (name:type)                                                             |
| v1.timestamp.status                                                                          | GET    | customer.verae.ai/v1/timestamp/status                                | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                                 | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                     | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                                 | POST   | customer.verae.ai/v1/timestamp                                       | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-12 — Receipts queue (waiting for final)

A visible queue of every hash not yet final, grouped by stage, fixing U-i3 (pending jobs hidden until 'Verify' tapped).



DC-12



DC-A6

| Features                                                                          |              |                                                                                 |                                                                                                                     |
|-----------------------------------------------------------------------------------|--------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Segment: Waiting / Final / All.                                                 |              | • Groups by stage — included (not final), pending, queued offline, final today. |                                                                                                                     |
| • Offline queue items with retry/backoff from auto_stamp.dart's persistent queue. |              | • Push (EP-044) + reconcile-on-launch explanation.                              |                                                                                                                     |
| • Offline tonal card; snackbar on reconnect with action.                          |              |                                                                                 |                                                                                                                     |
| Function / source references                                                      |              |                                                                                 |                                                                                                                     |
| lib/timestamps/timestamps_ui.dart TimestampsScreen                                |              |                                                                                 |                                                                                                                     |
| lib/timestamps/auto_stamp.dart (persistent queue, backoff)                        |              |                                                                                 |                                                                                                                     |
| lib/files/sync_queue.dart                                                         |              |                                                                                 |                                                                                                                     |
| lib/timestamps/auto_stamp.dart                                                    |              |                                                                                 |                                                                                                                     |
| lib/errors.dart                                                                   |              |                                                                                 |                                                                                                                     |
| API id                                                                            | Method       | Path                                                                            | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                               | GET          | customer.verae.ai/v1/timestamp/status                                           | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                                   | local + APIs | App add flow (DC-07D)                                                           | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJson!:string (JSONL), ... |
| peergos.cube                                                                      | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                                | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                      | POST         | customer.verae.ai/v1/timestamp                                                  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

DC-13 — Account & settings

Account, security, timestamp preferences, billing key and diagnostics in grouped iOS settings style.



| Features                                                                                                               |                                                                                                                            |
|------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| • Linked identity row (Verae + DataCube).                                                                              | • Security group: Face ID, 2FA (DC-04), change password, forget saved logins (existing strings).                           |
| • Timestamp preferences: auto-stamp, notify on final.                                                                  | • Billing: Usage & billing (DC-14) and the billing key (xVerae- token) masked.                                             |
| • Profile hero: avatar, email, Verae+DataCube linked chips, storage/stamps summary; tappable to edit profile (portal). | • Security group: BiometricPrompt toggle (Keystore), 2FA → DC-04/Android equivalent, change password, forget logins.       |
| • Timestamps group: auto-stamp + FCM notify-on-final (Verae signature = timestamp receipt).                            | • Billing group: Usage & billing (DC-14 companion) + masked xVerae- key; footer points to customer.verae.ai for Stripe/PO. |
| • Help: diagnostics + about. Bottom navigation Account selected (5 destinations).                                      | • Settings cards; Windows Hello replaces Face ID (credentials in Credential Locker).                                       |
| • AdwPreferencesDialog with pages General / Security / Billing.                                                        | • Billing key row with Rotate.                                                                                             |

Function / source references


lib/settings\_screen.dart SettingsScreen  
lib/diag/sign\_in\_diag.dart DiagPanel  
auth/change\_password.dart  
lib/auth/biometric\_login.dart  
lib/billing/usage\_billing\_screen.dart  
design DC-13  
lib/settings\_screen.dart

| API id              | Method          | Path                                             | Key params (name:type)                                                                                                       |
|---------------------|-----------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| v1.timestamp.status | GET             | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                                        |
| peergos.cube        | —               | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                   |
| v1.timestamp        | POST            | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                           |
| portal.profile      | GET/PATCH       | customer.verae.ai/portal/api/profile             | Authorization:header string, name,companyName,groupName,...string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| portal.usage        | GET             | customer.verae.ai/portal/api/usage               | peergosUsername:string?, from,to:ISO date?                                                                                   |
| portal.tokens       | GET/POST/DELETE | customer.verae.ai/portal/api/tokens              | name:string, id:string                                                                                                       |
| portal.login        | POST            | customer.verae.ai/portal/api/login               | email:string, password:string, totpCode:string (6 digits)                                                                    |
| portal.billing      | GET/POST        | customer.verae.ai/portal/api/billing/*           | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                              |
| portal.2fa          | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*               | setup:POST {}, code:string, totpCode:string                                                                                  |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

DC-14 — Usage & billing + billing key

Usage, charges and the billing key in-app; links to the zap portal for invoices and payment.



DC-14

DC-A14


DC-M14

| Features                                                                                                           |                 |                                                                  |                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------|-----------------|------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Tabs kept from current app: Usage / Billing / Cards / PO (PO only in staff mode).                                |                 | • Period summary with daily chart; chart has a text alternative. |                                                                                                                               |
| • Line items as units × price variables (P, Q); already-registered hits shown as not billed.                       |                 | • Billing key (xVeræ-) masked with rotate.                       |                                                                                                                               |
| • Price-variable disclaimer + portal link.                                                                         |                 | • Tabs Usage/Billing/Cards/PO.                                   |                                                                                                                               |
| • Chart + line items.                                                                                              |                 | • Billing key.                                                   |                                                                                                                               |
| • Stripe + PO.                                                                                                     |                 | • customer.verae.ai disclaimer.                                  |                                                                                                                               |
| • Tabs.                                                                                                            |                 | • Key rotate.                                                    |                                                                                                                               |
| Function / source references                                                                                       |                 |                                                                  |                                                                                                                               |
| lib/billing/usage_billing_screen.dart (_UsageTab, _BillingTab, _CardsTab, _PoTab, _Banner 'Showing sample data..') |                 |                                                                  |                                                                                                                               |
| lib/billing/billing_api.dart                                                                                       |                 |                                                                  |                                                                                                                               |
| lib/src/rust/api/billing_link.dart                                                                                 |                 |                                                                  |                                                                                                                               |
| lib/datacube/datacube_ui.dart                                                                                      |                 |                                                                  |                                                                                                                               |
| lib/auth/*                                                                                                         |                 |                                                                  |                                                                                                                               |
| lib/billing/*                                                                                                      |                 |                                                                  |                                                                                                                               |
| lib/signup_screen.dart                                                                                             |                 |                                                                  |                                                                                                                               |
| lib/billing/usage_billing_screen.dart                                                                              |                 |                                                                  |                                                                                                                               |
| API id                                                                                                             | Method          | Path                                                             | Key params (name:type)                                                                                                        |
| portal.usage                                                                                                       | GET             | customer.verae.ai/portal/api/usage                               | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                                                                                      | GET/POST/DELETE | customer.verae.ai/portal/api/tokens                              | name:string, id:string                                                                                                        |
| portal.login                                                                                                       | POST            | customer.verae.ai/portal/api/login                               | email:string, password:string, totpCode:string (6 digits)                                                                     |
| portal.billing                                                                                                     | GET/POST        | customer.verae.ai/portal/api/billing/*                           | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                                                                                     | GET/PATCH       | customer.verae.ai/portal/api/profile                             | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |

Sample calls + full param tables → VERÆ-API-REFERENCE.pdf

DC-15 — Offline & error handling

How the app behaves offline and on hard errors: hashes are captured and queued, nothing is lost, and actions needing the user are explicit.



DC-15


DC-L4

| Features                                                                                 |        |                                                                                  |                                                            |
|------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------|------------------------------------------------------------|
| • Persistent offline banner (not just a snackbar).                                       |        | • Queued items show their computed multihash so the user knows capture happened. |                                                            |
| • 'Action needed' errors (401/403) held, not dropped — mirrors printit's pending folder. |        | • AdwStatusPage with pill button.                                                |                                                            |
| • AdwToast for 'action needed'.                                                          |        |                                                                                  |                                                            |
| Function / source references                                                             |        |                                                                                  |                                                            |
| lib/errors.dart isOfflineError                                                           |        |                                                                                  |                                                            |
| lib/files/sync_queue.dart                                                                |        |                                                                                  |                                                            |
| lib/files/transfers.dart                                                                 |        |                                                                                  |                                                            |
| lib/timestamps/auto_stamp.dart                                                           |        |                                                                                  |                                                            |
| lib/errors.dart                                                                          |        |                                                                                  |                                                            |
| API id                                                                                   | Method | Path                                                                             | Key params (name:type)                                     |
| peergos.cube                                                                             | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                                 | username:string, password:string, path:string, bytes:bytes |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

DC-16 — Delete → tombstone confirmation

Deletes in a DataCube are tombstones: the file disappears but a timestamped block records the delete. The action sheet explains this before confirming.




| DC-16                                                                          |        |                                                       |                                                                                    |
|--------------------------------------------------------------------------------|--------|-------------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                       |        |                                                       |                                                                                    |
| • Action sheet copy explains tombstone semantics in plain words.               |        | • Destructive button wording 'Delete (keep history)'. |                                                                                    |
| Function / source references                                                   |        |                                                       |                                                                                    |
| lib/datacube/datacube_ui.dart (o.tombstoned, tombstoneBlock, 'deleted in ...') |        |                                                       |                                                                                    |
| lib/files/file_browser.dart delete dialog                                      |        |                                                       |                                                                                    |
| API id                                                                         | Method | Path                                                  | Key params (name:type)                                                             |
| v1.timestamp.status                                                            | GET    | customer.verae.ai/v1/timestamp/status                 | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                   | —      | peergos.verae.ai (Peergos HTTP/API + local rust)      | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                   | POST   | customer.verae.ai/v1/timestamp                        | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → [VERAE-API-REFERENCE.pdf](#)

DC-1 — Sign in (unified Verae + DataCube)

One sign-in for the Verae account (zap.verae.ai, timestamps, billing) and the Peergos DataCube account, resolving finding U-i10 (two accounts confuse users).




| Features                                                                                                                |                 |                                                                                                                                      |                                                                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Brand header with the Verae mark; plain-language promise of what the account covers.                                  |                 | • Primary action is biometric when saved logins exist (Keychain on iOS; KeyStore strong biometric on Android).                       |                                                                                                                                    |
| • Email + password fallback; password field shows focus ring (WCAG 2.4.7) and a reveal toggle with an accessible label. |                 | • Google sign-in kept from social_login.dart.                                                                                        |                                                                                                                                    |
| • Create account entry; Free plan copy taken from verae_first_login.dart.                                               |                 | • Advanced path for DataCube-only sign-in kept but de-emphasised.                                                                    |                                                                                                                                    |
| • BiometricPrompt (BIOMETRIC_STRONG, KeyStore-backed); declare USE_BIOMETRIC (U-a2 verify).                             |                 | • Outlined text fields with floating labels (M3).                                                                                    |                                                                                                                                    |
| • Credential Manager for Google / passkeys.                                                                             |                 | • Sidebar (source list): cubes with counts, Shared with me, Library (Receipts count = waiting). Replaces the Material drawer (U-w5). |                                                                                                                                    |
| • Waiting-receipts banner.                                                                                              |                 | • Sortable table: name, size, short multihash, receipt badge, added time; tombstones struck through.                                 |                                                                                                                                    |
| Function / source references                                                                                            |                 |                                                                                                                                      |                                                                                                                                    |
| lib/main.dart LoginScreen                                                                                               |                 |                                                                                                                                      |                                                                                                                                    |
| lib/auth/verae_first_login.dart VeraeLoginScreen                                                                        |                 |                                                                                                                                      |                                                                                                                                    |
| auth/biometric_login.dart                                                                                               |                 |                                                                                                                                      |                                                                                                                                    |
| auth/social_login.dart                                                                                                  |                 |                                                                                                                                      |                                                                                                                                    |
| auth/saved_logins.dart                                                                                                  |                 |                                                                                                                                      |                                                                                                                                    |
| lib/main.dart                                                                                                           |                 |                                                                                                                                      |                                                                                                                                    |
| lib/auth/biometric_login.dart (KeyStore strong biometric)                                                               |                 |                                                                                                                                      |                                                                                                                                    |
| lib/datacube/datacube_ui.dart                                                                                           |                 |                                                                                                                                      |                                                                                                                                    |
| lib/files/file_browser.dart (drawer, desktop_drop, 'Save to computer')                                                  |                 |                                                                                                                                      |                                                                                                                                    |
| lib/files/item_detail.dart                                                                                              |                 |                                                                                                                                      |                                                                                                                                    |
| API id                                                                                                                  | Method          | Path                                                                                                                                 | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                                                                                     | GET             | customer.verae.ai/v1/timestamp/status                                                                                                | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                                                                                            | —               | peergos.verae.ai (Peergos HTTP/API + local rust)                                                                                     | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                                                                                           | POST            | sign.verae.ai/sign/v1/requests                                                                                                       | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                                                                                            | POST            | customer.verae.ai/v1/timestamp                                                                                                       | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| portal.usage                                                                                                            | GET             | customer.verae.ai/portal/api/usage                                                                                                   | peergosUsername:string?, from,to:ISO date?                                                                                         |
| portal.tokens                                                                                                           | GET/POST/DELETE | customer.verae.ai/portal/api/tokens                                                                                                  | name:string, id:string                                                                                                             |
| portal.login                                                                                                            | POST            | customer.verae.ai/portal/api/login                                                                                                   | email:string, password:string, totpCode:string (6 digits)                                                                          |
| portal.billing                                                                                                          | GET/POST        | customer.verae.ai/portal/api/billing/*                                                                                               | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                                    |
| portal.profile                                                                                                          | GET/PATCH       | customer.verae.ai/portal/api/profile                                                                                                 | Authorization:header string, name,companyName,groupName,...string, billingType:'stripe' 'purchase_order', phone:string E.164       |
| sign.public.sign                                                                                                        | POST            | sign.verae.ai/sign/v1/public/:token/sign                                                                                             | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → [VERAE-API-REFERENCE.pdf](#)

DC-2 — DataCube list (home)

Home screen: all cubes with an at-a-glance evidence status per cube and a global 'receipts waiting' indicator.




| Features                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>• Global pending banner (U-i3): count of not-final receipts with a jump to the Receipts queue.</li><li>• Cube rows: cube glyph, size, chain health, status badge with text (never colour only).</li><li>• Tonal warning card for pending receipts.</li><li>• Extended FAB 'New DataCube' (collapses on scroll); navigation bar with 5 destinations; predictive back (U-a3).</li><li>• Progress HUD: per-file hashing (Rust core streaming), 'Already registered' instant receipt, pending state; cancel with ■.</li><li>• Tray flyout from the notification-area icon (gold dot = waiting).</li></ul> | <ul style="list-style-type: none"><li>• Filter chips incl. 'Attention'.</li><li>• Sync + storage line (billing context).</li><li>• M3 filter chips with check icon when selected.</li><li>• Full-window drop target naming the destination (desktop_drop today).</li><li>• Toast (AppNotification) with Open receipt / Certificate.</li><li>• (1–5 as DC-08) in Cantarell / Adwaita styling. Notification works in Flatpak — U-I3.</li></ul> |

| Function / source references                                                                    |              |                                                  |                                                                                                                     |
|-------------------------------------------------------------------------------------------------|--------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| lib/datacube/datacube_ui.dart CubeListScreen, DataCubesEdgeTab (empty text 'No DataCubes yet.') |              |                                                  |                                                                                                                     |
| lib/datacube/datacube_ui.dart CubeListScreen                                                    |              |                                                  |                                                                                                                     |
| file_browser.dart bottom bar                                                                    |              |                                                  |                                                                                                                     |
| lib/files/file_browser.dart (desktop_drop)                                                      |              |                                                  |                                                                                                                     |
| lib/datacube/datacube_ui.dart (drag-and-drop, commit 79fd3bf)                                   |              |                                                  |                                                                                                                     |
| New (U-w3)                                                                                      |              |                                                  |                                                                                                                     |
| lib/timestamps/timestamps_ui.dart                                                               |              |                                                  |                                                                                                                     |
| New                                                                                             |              |                                                  |                                                                                                                     |
| API id                                                                                          | Method       | Path                                             | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                                             | GET          | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                                                 | local + APIs | App add flow (DC-07D)                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                                                    | —            | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                                    | POST         | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERA-E-API-REFERENCE.pdf

DC-3 — Cube detail — files with receipt states


Shows a cube's files, each with its receipt state per George's rule, plus tombstoned (deleted) entries kept in history.



DC-06

DC-A3

DC-M3



DC-W3

DC-L3



| Features                                                                                                                                                                                          |                                                                                                                                                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>Cube header: owner, block count, chain verification time, share count.</li><li>'Show deleted' toggle (CheckedPopupMenuItem 'Show deleted' today).</li></ul> | <ul style="list-style-type: none"><li>Primary cube actions: Chain (DC-09), Verify (DC-10), Share (DC-11).</li></ul>                                                                                                                     |
| <ul style="list-style-type: none"><li>Add file → DC-07 (Files, Photos, Camera, Scan).</li><li>M3 modal bottom sheet replaces the iOS action sheet.</li></ul>                                      | <ul style="list-style-type: none"><li>File rows: name, size, short multihash, receipt badge: Final · #N / #N · not final / Pending receipt / Existing / Queued offline. Tombstones struck through with 'Deleted in block 54'.</li></ul> |
| <ul style="list-style-type: none"><li>Chain table with event type, prev/this hash, per-block Substrate state; tombstone row selectable.</li></ul>                                                 | <ul style="list-style-type: none"><li>Same receipt badges as iOS (shared component).</li></ul>                                                                                                                                          |
| <ul style="list-style-type: none"><li>Settings cards; Windows Hello replaces Face ID (credentials in Credential Locker).</li></ul>                                                                | <ul style="list-style-type: none"><li>WorkManager for queued uploads and receipt reconcile (U-a5) with a foreground progress notification.</li></ul>                                                                                    |
|                                                                                                                                                                                                   | <ul style="list-style-type: none"><li>Window-modal sheet (HIG) with check list and Export Report.</li></ul>                                                                                                                             |
|                                                                                                                                                                                                   | <ul style="list-style-type: none"><li>AdwPreferencesDialog with pages General / Security / Billing.</li></ul>                                                                                                                           |

| Function / source references                                                                             |                 |                                                  |                                                                                                                     |
|----------------------------------------------------------------------------------------------------------|-----------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| lib/datacube/datacube_ui.dart CubeScreen (tombstoned rows, 'Show deleted', 'Timestamp un-stamped files') |                 |                                                  |                                                                                                                     |
| lib/datacube/datacube_ui.dart CubeScreen                                                                 |                 |                                                  |                                                                                                                     |
| files/sync_queue.dart                                                                                    |                 |                                                  |                                                                                                                     |
| lib/datacube/datacube_ui.dart CubeChainScreen, CubeVerifyScreen                                          |                 |                                                  |                                                                                                                     |
| lib/settings_screen.dart                                                                                 |                 |                                                  |                                                                                                                     |
| lib/files/file_browser.dart                                                                              |                 |                                                  |                                                                                                                     |
| lib/timestamps/auto_stamp.dart                                                                           |                 |                                                  |                                                                                                                     |
| API id                                                                                                   | Method          | Path                                             | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                                                      | GET             | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                               |
| peergos.cube                                                                                             | —               | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                                             | POST            | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |
| portal.login                                                                                             | POST            | customer.verae.ai/portal/api/login               | email:string, password:string, totpCode:string (6 digits)                                                           |
| portal.2fa                                                                                               | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*               | setup:POST {}, code:string, totpCode:string                                                                         |
| add.destination                                                                                          | local + APIs    | App add flow (DC-07D)                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

DC-4 — Receipt restamp timeline — expandable JSONL + diffs

Shows a file's original timestamp receipt and each restamp with additional JSONL payloads. Entries expand to nested JSON and per-field diff history.




| Features                                                                        |              |                                                             |                                                                                                                      |
|---------------------------------------------------------------------------------|--------------|-------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| • Header: file, sha256, restamp count.                                          |              | • Timeline newest-first; expand/collapse.                   |                                                                                                                      |
| • Expanded: pretty JSONL nested object + diff history list (path, op, from/to). |              | • restampOf link to parent job.                             |                                                                                                                      |
| • Original receipt footer (no additional data).                                 |              | • Contract note: restamp:true; digests of additional JSONL. |                                                                                                                      |
| • M3 top app bar.                                                               |              | • Expandable cards.                                         |                                                                                                                      |
| • JSONL + diff list.                                                            |              | • Original footer.                                          |                                                                                                                      |
| • Split: timeline   detail.                                                     |              | • JSONL pretty + diff table.                                |                                                                                                                      |
| Function / source references                                                    |              |                                                             |                                                                                                                      |
| lib/timestamps/*                                                                |              |                                                             |                                                                                                                      |
| CORE-CONTRACT restampOf                                                         |              |                                                             |                                                                                                                      |
| archive JSONL additional                                                        |              |                                                             |                                                                                                                      |
| lib/main.dart                                                                   |              |                                                             |                                                                                                                      |
| lib/errors.dart                                                                 |              |                                                             |                                                                                                                      |
| New                                                                             |              |                                                             |                                                                                                                      |
| API id                                                                          | Method       | Path                                                        | Key params (name:type)                                                                                               |
| v1.timestamp.status                                                             | GET          | customer.verae.ai/v1/timestamp/status                       | sha256:string (64 hex), jobId:string?                                                                                |
| peergos.cube                                                                    | —            | peergos.verae.ai (Peergos HTTP/API + local rust)            | username:string, password:string, path:string, bytes:bytes                                                           |
| v1.timestamp                                                                    | POST         | customer.verae.ai/v1/timestamp                              | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                   |
| portal.login                                                                    | POST         | customer.verae.ai/portal/api/login                          | email:string, password:string, totpCode:string (6 digits)                                                            |
| add.destination                                                                 | local + APIs | App add flow (DC-07D)                                       | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadata.Jsonl:string (JSONL), ... |

Sample calls + full param tables → VERA-E-API-REFERENCE.pdf

DC-5 — Share & revoke (Peergos)

Share a cube or file with Peergos users/groups or a link; revoke access. Shares and revokes are cube-chain blocks with their own timestamps.




| Features                                                                                     |        |                                                                      |                                                                                    |
|----------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Chain-recording explanation (existing copy, elevated).                                     |        | • Invite by Peergos username/email with view/edit segmented control. |                                                                                    |
| • Access list with Remove (destructive style + confirmation).                                |        | • Links with expiry and Revoke.                                      |                                                                                    |
| • Channels: new link, SMS (existing 'Send by text'), iOS share sheet.                        |        | • Full-screen dialog pattern on compact width (M3).                  |                                                                                    |
| • Android sharesheet with direct-share targets; revoke uses an M3 dialog (same copy as iOS). |        | • Popover anchored to the Share toolbar button; same content as iOS. |                                                                                    |
| • System share menu (Mail, Messages, AirDrop).                                               |        |                                                                      |                                                                                    |
| Function / source references                                                                 |        |                                                                      |                                                                                    |
| lib/sharing/sharing_ui.dart ShareScreen, _NewLinkDialog, PeopleScreen, LinksScreen           |        |                                                                      |                                                                                    |
| lib/src/rust/api/sharing.dart revokeAccess                                                   |        |                                                                      |                                                                                    |
| lib/sharing/sharing_ui.dart (share sheet)                                                    |        |                                                                      |                                                                                    |
| lib/sharing/sharing_ui.dart                                                                  |        |                                                                      |                                                                                    |
| API id                                                                                       | Method | Path                                                                 | Key params (name:type)                                                             |
| v1.timestamp.status                                                                          | GET    | customer.verae.ai/v1/timestamp/status                                | sha256:string (64 hex), jobld:string?                                              |
| peergos.cube                                                                                 | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                     | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                                 | POST   | customer.verae.ai/v1/timestamp                                       | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

DC-6 — Receipts queue (waiting for final)

A visible queue of every hash not yet final, grouped by stage, fixing U-i3 (pending jobs hidden until 'Verify' tapped).




| Features                                                                          |                 |                                                                                 |                                                                                                                               |
|-----------------------------------------------------------------------------------|-----------------|---------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Segment: Waiting / Final / All.                                                 |                 | • Groups by stage — included (not final), pending, queued offline, final today. |                                                                                                                               |
| • Offline queue items with retry/backoff from auto_stamp.dart's persistent queue. |                 | • Push (EP-044) + reconcile-on-launch explanation.                              |                                                                                                                               |
| • Offline tonal card; snackbar on reconnect with action.                          |                 | • Settings toolbar tabs: Account, Security, Timestamps, Billing, Advanced.      |                                                                                                                               |
| • Billing pane: plan, usage, billing key rotate/copy, portal link.                |                 | • Price-variable note.                                                          |                                                                                                                               |
| Function / source references                                                      |                 |                                                                                 |                                                                                                                               |
| lib/timestamps/timestamps_ui.dart TimestampsScreen                                |                 |                                                                                 |                                                                                                                               |
| lib/timestamps/auto_stamp.dart (persistent queue, backoff)                        |                 |                                                                                 |                                                                                                                               |
| lib/files/sync_queue.dart                                                         |                 |                                                                                 |                                                                                                                               |
| lib/timestamps/auto_stamp.dart                                                    |                 |                                                                                 |                                                                                                                               |
| lib/errors.dart                                                                   |                 |                                                                                 |                                                                                                                               |
| lib/settings_screen.dart                                                          |                 |                                                                                 |                                                                                                                               |
| lib/billing/usage_billing_screen.dart                                             |                 |                                                                                 |                                                                                                                               |
| API id                                                                            | Method          | Path                                                                            | Key params (name:type)                                                                                                        |
| v1.timestamp.status                                                               | GET             | customer.verae.ai/v1/timestamp/status                                           | sha256:string (64 hex), jobId:string?                                                                                         |
| peergos.cube                                                                      | —               | peergos.verae.ai (Peergos HTTP/API + local rust)                                | username:string, password:string, path:string, bytes:bytes                                                                    |
| v1.timestamp                                                                      | POST            | customer.verae.ai/v1/timestamp                                                  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                            |
| portal.usage                                                                      | GET             | customer.verae.ai/portal/api/usage                                              | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                                                     | GET/POST/DELETE | customer.verae.ai/portal/api/tokens                                             | name:string, id:string                                                                                                        |
| portal.billing                                                                    | GET/POST        | customer.verae.ai/portal/api/billing/*                                          | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                                                    | GET/PATCH       | customer.verae.ai/portal/api/profile                                            | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| add.destination                                                                   | local + APIs    | App add flow (DC-07D)                                                           | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ...           |

Sample calls + full param tables → VERAEE-API-REFERENCE.pdf

## DC-JL1 — Expandable JSONL data builder + previous tags

Full-screen nested JSONL builder; previous tags selectable; diff history.




## DC-JL1

| Features                         |              |                                                  |                                                                                                                     |
|----------------------------------|--------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Previous tags.                 |              | • Nested builder.                                |                                                                                                                     |
| • Diffs.                         |              | • Use in flow.                                   |                                                                                                                     |
| Function / source references     |              |                                                  |                                                                                                                     |
| lib/files/*                      |              |                                                  |                                                                                                                     |
| lib/datacube/*                   |              |                                                  |                                                                                                                     |
| lib/timestamps/*                 |              |                                                  |                                                                                                                     |
| peergos                          |              |                                                  |                                                                                                                     |
| customer.verae.ai/v1/timestamp   |              |                                                  |                                                                                                                     |
| lib/timestamps/* (restamp JSONL) |              |                                                  |                                                                                                                     |
| design DC-JL1 builder            |              |                                                  |                                                                                                                     |
| API id                           | Method       | Path                                             | Key params (name:type)                                                                                              |
| add.destination                  | local + APIs | App add flow (DC-07D)                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                     | —            | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                     | POST         | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → [VERAE-API-REFERENCE.pdf](#)

DC-7 — Menu bar extra + notifications

Ambient status on macOS: a menu bar extra with waiting receipts and quick actions; User Notifications when a receipt is final.



DC-M7


DC-W2

| Features                                                                                            |        |                                                                     |                                                                                    |
|-----------------------------------------------------------------------------------------------------|--------|---------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Menu bar extra (MenuBarExtra) listing not-final receipts with stage text; global hotkey to stamp. |        | • Notification on finality with Open / Certificate actions.         |                                                                                    |
| • Toast (AppNotification) with Open receipt / Certificate.                                          |        | • Tray flyout from the notification-area icon (gold dot = waiting). |                                                                                    |
| Function / source references                                                                        |        |                                                                     |                                                                                    |
| New (Mac equivalent of U-w3/U-l3)                                                                   |        |                                                                     |                                                                                    |
| New (U-w3)                                                                                          |        |                                                                     |                                                                                    |
| API id                                                                                              | Method | Path                                                                | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                 | GET    | customer.verae.ai/v1/timestamp/status                               | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                                        | POST   | customer.verae.ai/v1/timestamp                                      | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERA-API-REFERENCE.pdf

## DC-8 — Offline & error states (Mac)

DC-15 on Mac: stacked banners above the table; toolbar offline pill.




DC-M8

| Features                          |        |                                                  |                                                            |
|-----------------------------------|--------|--------------------------------------------------|------------------------------------------------------------|
| • Offline banner with queue link. |        | • Action-needed banner; held items.              |                                                            |
| Function / source references      |        |                                                  |                                                            |
| lib/errors.dart                   |        |                                                  |                                                            |
| lib/files/sync_queue.dart         |        |                                                  |                                                            |
| API id                            | Method | Path                                             | Key params (name:type)                                     |
| peergos.cube                      | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes |

Sample calls + full param tables → VERA-API-REFERENCE.pdf

IT-01 — Device enrollment & shift sign-in

Per-shift sign-in on an enrolled device. Events are signed by the device key and carry actor + device (doc 02 §1).



| IT-01                                                                                          |        |                                                        |                                                                                    |
|------------------------------------------------------------------------------------------------|--------|--------------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                                       |        |                                                        |                                                                                    |
| • Enrolled-device card (authentik OIDC device flow; Ed25519 key in Keystore / Secure Enclave). |        | • Badge scan sign-in: 72 dp primary target for gloves. |                                                                                    |
| • SSO alternative.                                                                             |        | • Location privacy statement (doc 02 'Privacy').       |                                                                                    |
| Function / source references                                                                   |        |                                                        |                                                                                    |
| itad-provenance/docs/02 §1 (who)                                                               |        |                                                        |                                                                                    |
| 10                                                                                             |        |                                                        |                                                                                    |
| peergos-flutter lib/auth/*                                                                     |        |                                                        |                                                                                    |
| API id                                                                                         | Method | Path                                                   | Key params (name:type)                                                             |
| v1.timestamp                                                                                   | POST   | customer.verae.ai/v1/timestamp                         | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

IT-02 — Field home — iOS

IT-02 with HIG: large title, tab bar, Live Activity for the custody session, and the blue location indicator.



IT-11

IT-02

| Features                                                                                                               |        |                                                                 |                                                                                    |
|------------------------------------------------------------------------------------------------------------------------|--------|-----------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Status badges; iOS shows the system location indicator + a Live Activity on the Lock Screen during custody sessions. |        | • Large scan button (VisionKit DataScannerViewController).      |                                                                                    |
| • Secondary actions as bordered buttons; no hardware scan key on iPhone (MFi ring scanners optional).                  |        | • Lot context: customer, site, manifest count.                  |                                                                                    |
| • 96 dp scan button + hardware scan key (Zebra DataWedge / Honeywell intents).                                         |        | • Last scanned list with evidence completeness (photos needed). |                                                                                    |
| • Check-in (GPS GeoFix + server time) and Hand off (QR) as large tonal actions.                                        |        | • Live counts and the pickup form's receipt status.             |                                                                                    |
| Function / source references                                                                                           |        |                                                                 |                                                                                    |
| itad-provenance/docs/02 §1                                                                                             |        |                                                                 |                                                                                    |
| 22 §2.1                                                                                                                |        |                                                                 |                                                                                    |
| itad-provenance/docs/22 §4.1                                                                                           |        |                                                                 |                                                                                    |
| 02 §1                                                                                                                  |        |                                                                 |                                                                                    |
| 13 §3–4                                                                                                                |        |                                                                 |                                                                                    |
| API id                                                                                                                 | Method | Path                                                            | Key params (name:type)                                                             |
| v1.timestamp                                                                                                           | POST   | customer.verae.ai/v1/timestamp                                  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

IT-03 — Scanner — iOS (VisionKit)

IT-03 on iOS: DataScannerViewController with item highlighting; result in a sheet.




| IT-12                                                                     |        | IT-03                                                                      |                                                                                    |
|---------------------------------------------------------------------------|--------|----------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                  |        |                                                                            |                                                                                    |
| • VisionKit highlights recognised codes/text; tap to choose when several. |        | • Result sheet with HIG buttons; haptic (UINotificationFeedbackGenerator). |                                                                                    |
| • Viewfinder with scan line; works with gloves (no tap needed).           |        | • Supported symbologies; NFC toggle for NTAG labels.                       |                                                                                    |
| • Result sheet: matched manifest line, or 'Not on manifest → Extra'.      |        | • Large next actions; photo hashing on capture.                            |                                                                                    |
| Function / source references                                              |        |                                                                            |                                                                                    |
| itad-provenance/docs/02 §1                                                |        |                                                                            |                                                                                    |
| 22 §2.1                                                                   |        |                                                                            |                                                                                    |
| itad-provenance/docs/02 §1 (Identify)                                     |        |                                                                            |                                                                                    |
| 22 U-i7/U-a2 (no scanner today)                                           |        |                                                                            |                                                                                    |
| API id                                                                    | Method | Path                                                                       | Key params (name:type)                                                             |
| v1.timestamp.status                                                       | GET    | customer.verae.ai/v1/timestamp/status                                      | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                              | POST   | customer.verae.ai/v1/timestamp                                             | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

### IT-04 — RFID bulk read (cage count)

BLE UHF RFID sled reads a whole cage; results reconcile against the manifest.




IT-04

| Features                                                     |        |                                                                                    |
|--------------------------------------------------------------|--------|------------------------------------------------------------------------------------|
| • Live count vs manifest with progress ring (number + text). |        | • Filter chips: matched / extra / missing.                                         |
| • Trigger-to-read action (hardware trigger on sled).         |        |                                                                                    |
| Function / source references                                 |        |                                                                                    |
| itad-provenance/docs/02 §1 (BLE UHF RFID sleds)              |        |                                                                                    |
| API id                                                       | Method | Path                                                                               |
| v1.timestamp                                                 | POST   | customer.verae.ai/v1/timestamp                                                     |
|                                                              |        | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-05 — Pickup check-in (GPS GeoFix)

Records arrival at the pickup site with GPS accuracy, seal, truck and photos; starts the custody session check-ins (every 5 min by default).




IT-05

| Features                                                       |        |                                                                                              |                                                                                    |
|----------------------------------------------------------------|--------|----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Map with geofence and accuracy circle.                       |        | • Geofence status + time source note (server time on sync; device time is captured_at only). |                                                                                    |
| • Seal and truck fields (scan-to-fill).                        |        | • Photo evidence hashed on device (SHA-256 in the event).                                    |                                                                                    |
| Function / source references                                   |        |                                                                                              |                                                                                    |
| itad-provenance/docs/02 \$1 (Where, custody check-in sequence) |        |                                                                                              |                                                                                    |
| 13 \$4                                                         |        |                                                                                              |                                                                                    |
| API id                                                         | Method | Path                                                                                         | Key params (name:type)                                                             |
| peergos.cube                                                   | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                                             | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                   | POST   | customer.verae.ai/v1/timestamp                                                               | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

IT-06 — Item capture — photos & identity

Per-item evidence: photos (hashed on device), serial, model and flags; feeds Intake (doc 13 §6).




IT-06

| Features                                                  |        |                                                  |                                                                                    |
|-----------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Photo strip with required slots (label, front, screen). |        | • Identity fields; serial confirmed from scan.   |                                                                                    |
| • Flags: data-bearing, battery (hazmat), asset tag alias. |        |                                                  |                                                                                    |
| Function / source references                              |        |                                                  |                                                                                    |
| itad-provenance/docs/02 §1 (Evidence)                     |        |                                                  |                                                                                    |
| 13 §6                                                     |        |                                                  |                                                                                    |
| lib/files/file_browser.dart                               |        |                                                  |                                                                                    |
| lib/timestamps/auto_stamp.dart                            |        |                                                  |                                                                                    |
| API id                                                    | Method | Path                                             | Key params (name:type)                                                             |
| peergos.cube                                              | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                              | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

IT-07 — Custody hand-off — QR exchange

Two-party custody transfer (driver ↔ dock). The giver shows a one-time QR; the receiver scans; both sign (gap 5 in doc 22 §3).



IT-07

| Features                                         |        |                                                                      |                                                                                                                                    |
|--------------------------------------------------|--------|----------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • One-time QR with lot, transfer ULID and nonce. |        | • Summary of what is being transferred (items, seal state, parties). |                                                                                                                                    |
| • Explains signing and receipt.                  |        | • NFC tap alternative.                                               |                                                                                                                                    |
| Function / source references                     |        |                                                                      |                                                                                                                                    |
| itad-provenance/docs/13 §4                       |        |                                                                      |                                                                                                                                    |
| 02 §1 (custody check-in sequence)                |        |                                                                      |                                                                                                                                    |
| 22 §3 gap 5                                      |        |                                                                      |                                                                                                                                    |
| lib/files/file_browser.dart                      |        |                                                                      |                                                                                                                                    |
| lib/timestamps/auto_stamp.dart                   |        |                                                                      |                                                                                                                                    |
| API id                                           | Method | Path                                                                 | Key params (name:type)                                                                                                             |
| v1.timestamp.status                              | GET    | customer.verae.ai/v1/timestamp/status                                | sha256:string (64 hex), jobId:string?                                                                                              |
| sign.requests                                    | POST   | sign.verae.ai/sign/v1/requests                                       | documentSha256:string 64 hex, documentName:string, signers:array<(email:string,name?:string)>, title:string?, message:string?, ... |
| sign.public.sign                                 | POST   | sign.verae.ai/sign/v1/public/:token/sign                             | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |
| v1.timestamp                                     | POST   | customer.verae.ai/v1/timestamp                                       | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-08 — Signature — iOS (PencilKit)

IT-08 on iOS using PencilKit canvas; Apple Pencil on iPad dock tablets.



| IT-13                                                                         |        | IT-08                                     |                                                                                    |
|-------------------------------------------------------------------------------|--------|-------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                      |        |                                           |                                                                                    |
| • PencilKit canvas; VoiceOver alternative: typed name + Face ID confirmation. |        | • Primary action at bottom per HIG.       |                                                                                    |
| • Plain-language statement of what is accepted.                               |        | • Signature pad with clear; large target. |                                                                                    |
| • Other party's status (signed on their device).                              |        | • Privacy note (doc 07 §4.1 p.staff).     |                                                                                    |
| Function / source references                                                  |        |                                           |                                                                                    |
| itad-provenance/docs/02 §1                                                    |        |                                           |                                                                                    |
| 22 §2.1                                                                       |        |                                           |                                                                                    |
| itad-provenance/docs/07 §4.1                                                  |        |                                           |                                                                                    |
| 13 §4, §11, §17 (signature on phone)                                          |        |                                           |                                                                                    |
| API id                                                                        | Method | Path                                      | Key params (name:type)                                                             |
| v1.timestamp.status                                                           | GET    | customer.verae.ai/v1/timestamp/status     | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                  | POST   | customer.verae.ai/v1/timestamp            | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-09 — Grading — iOS

IT-09 on iOS: segmented control for functional status; same grade scale.



IT-I4


IT-09

| Features                                                                      |        |                                                                       |                                                                                    |
|-------------------------------------------------------------------------------|--------|-----------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Grade buttons ≥ 58 pt.                                                      |        | • UISegmentedControl for functional status.                           |                                                                                    |
| • AI proposal banner with model/version and confidence (DecisionAgent input). |        | • Six large grade targets A+...F with descriptions (not colour only). |                                                                                    |
| • Functional status chips.                                                    |        | • Confirm action names the grade.                                     |                                                                                    |
| Function / source references                                                  |        |                                                                       |                                                                                    |
| itad-provenance/docs/02 §1                                                    |        |                                                                       |                                                                                    |
| 22 §2.1                                                                       |        |                                                                       |                                                                                    |
| itad-provenance/docs/02 §2.2                                                  |        |                                                                       |                                                                                    |
| 13 §6                                                                         |        |                                                                       |                                                                                    |
| API id                                                                        | Method | Path                                                                  | Key params (name:type)                                                             |
| v1.timestamp.status                                                           | GET    | customer.verae.ai/v1/timestamp/status                                 | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                  | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                      | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                  | POST   | customer.verae.ai/v1/timestamp                                        | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

IT-10 — Floor mode — shred bin (and wipe check)

Floor use of the mobile app: scan serials into a shred bin with scale reading and CCTV reference; failed wipes flow here (doc 13 §7–8). The full wipe/shred stations are IT-S5/S6.




IT-10

| Features                                                                  |        |                                                              |                                                                                    |
|---------------------------------------------------------------------------|--------|--------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Batch header with machine, particle size, scale reading (MQTT, stable). |        | • Serial list with reason (failed wipe / requested destroy). |                                                                                    |
| • Commingled-batch rule explained.                                        |        | • Scan / Start shred actions.                                |                                                                                    |
| Function / source references                                              |        |                                                              |                                                                                    |
| itad-provenance/docs/13 §7-8                                              |        |                                                              |                                                                                    |
| 02 §2 (shredder station)                                                  |        |                                                              |                                                                                    |
| API id                                                                    | Method | Path                                                         | Key params (name:type)                                                             |
| v1.timestamp.status                                                       | GET    | customer.verae.ai/v1/timestamp/status                        | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                              | —      | peergos.verae.ai (Peergos HTTP/API + local rust)             | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                              | POST   | customer.verae.ai/v1/timestamp                               | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-11 — Offline queue

Offline-first capture: signed events queue locally (SQLite) and upload to itad-mobile-sync; status shows what is safe vs still waiting.



IT-11

| Features                                                           |              |                                                                   |                                                                                                                      |
|--------------------------------------------------------------------|--------------|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| • Persistent offline banner with duration and reassurance.         |              | • Queue of signed events (device key) with capture time and size. |                                                                                                                      |
| • Time semantics (captured_at vs received_at) and buffer capacity. |              |                                                                   |                                                                                                                      |
| Function / source references                                       |              |                                                                   |                                                                                                                      |
| itad-provenance/docs/02 §1 (Offline)                               |              |                                                                   |                                                                                                                      |
| 22 §3 gap 8                                                        |              |                                                                   |                                                                                                                      |
| API id                                                             | Method       | Path                                                              | Key params (name:type)                                                                                               |
| add.destination                                                    | local + APIs | App add flow (DC-07D)                                             | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadata.Jsonl:string (JSONL), ... |
| peergos.cube                                                       | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                  | username:string, password:string, path:string, bytes:bytes                                                           |
| v1.timestamp                                                       | POST         | customer.verae.ai/v1/timestamp                                    | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                   |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## IT-12 — Glove / outdoor (sunlight) mode

High-contrast, oversized layout for gloves and direct sunlight: ≥ 120 dp targets, black/yellow palette (21:1 / 19.6:1 contrast), haptics, hardware keys.




IT-12

| Features                                                                |        |                                          |                                                                                    |
|-------------------------------------------------------------------------|--------|------------------------------------------|------------------------------------------------------------------------------------|
| • Giant scan target; one-hand reach.                                    |        | • Two large secondary actions.           |                                                                                    |
| • Last scan readout in 20 sp+ type with symbol + word.                  |        | • Gesture and hardware-key alternatives. |                                                                                    |
| Function / source references                                            |        |                                          |                                                                                    |
| itad-provenance/docs/22 U-i9, U-a6 (glove-size targets, sunlight theme) |        |                                          |                                                                                    |
| API id                                                                  | Method | Path                                     | Key params (name:type)                                                             |
| v1.timestamp.status                                                     | GET    | customer.verae.ai/v1/timestamp/status    | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                            | POST   | customer.verae.ai/v1/timestamp           | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

### IT-13 — Lot receipts & custody timeline

Per-lot evidence status: every event's receipt state, custody legs and documents, using the shared receipt badge.




IT-13

| Features                                |        |                                                  |                                                                                    |
|-----------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Lot evidence progress (final vs not). |        | • Custody timeline rows with state.              |                                                                                    |
| • Rule reminder.                        |        |                                                  |                                                                                    |
| Function / source references            |        |                                                  |                                                                                    |
| itad-provenance/docs/06                 |        |                                                  |                                                                                    |
| 16 \$6                                  |        |                                                  |                                                                                    |
| 22 \$4.4                                |        |                                                  |                                                                                    |
| API id                                  | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status                     | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobld:string?                                              |
| peergos.cube                            | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                            | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## IT-C1 — Customer portal — lots

Customer view of lots with lifecycle status and evidence state; entry to items, certificates and settlements (doc 21 §10).




IT-C1

| Features                                                    |        |                                                  |                                                                                    |
|-------------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Lots table with evidence column (receipt states roll-up). |        | • Summary KPIs.                                  |                                                                                    |
| Function / source references                                |        |                                                  |                                                                                    |
| itad-provenance/docs/21 §10                                 |        |                                                  |                                                                                    |
| 15 §7                                                       |        |                                                  |                                                                                    |
| API id                                                      | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status                                         | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-C2 — Customer portal — lot detail

Lot progress and items with per-item status and evidence state.




## IT-C2

| Features                          |        |                                         |                                                                                    |
|-----------------------------------|--------|-----------------------------------------|------------------------------------------------------------------------------------|
| • Lifecycle chips.                |        | • Items table with status and evidence. |                                                                                    |
| • Certificate timing explanation. |        |                                         |                                                                                    |
| Function / source references      |        |                                         |                                                                                    |
| itad-provenance/docs/21 §10       |        |                                         |                                                                                    |
| API id                            | Method | Path                                    | Key params (name:type)                                                             |
| v1.timestamp                      | POST   | customer.verae.ai/v1/timestamp          | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

IT-C3 — Item history — mobile web

IT-C3 reflowed for phones (buyers scanning an asset's QR label).




| IT-C7                        |        |                                |                                                                                    |
|------------------------------|--------|--------------------------------|------------------------------------------------------------------------------------|
| Features                     |        |                                |                                                                                    |
| • Summary badges wrap.       |        | • Single-column history.       |                                                                                    |
| Function / source references |        |                                |                                                                                    |
| itad-provenance/docs/09 §4   |        |                                |                                                                                    |
| API id                       | Method | Path                           | Key params (name:type)                                                             |
| v1.timestamp                 | POST   | customer.verae.ai/v1/timestamp | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## IT-C4 — Certificate view + verify

Customer certificate with final receipt, signers, verify QR, downloads and validity/revocation status (doc 15 §4–5).




IT-C4

| Features                                                         |        |                                                  |                                                                                    |
|------------------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Certificate preview with receipt state, signers and multihash. |        | • Verify QR + downloads.                         |                                                                                    |
| • Validity / revocation / revision status.                       |        |                                                  |                                                                                    |
| Function / source references                                     |        |                                                  |                                                                                    |
| itad-provenance/docs/15 §4-5                                     |        |                                                  |                                                                                    |
| 13 §23                                                           |        |                                                  |                                                                                    |
| API id                                                           | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status                                              | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                     | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                     | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## IT-C5 — Request pickup & quote

Pickup request wizard with an estimate; becomes a sales quote (EP-110).




IT-C5

| Features                                    |        |                                                  |                                                                                    |
|---------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Stepper.                                  |        | • Asset counts.                                  |                                                                                    |
| • Service options incl. hazmat and witness. |        | • Estimate with units × P disclaimer.            |                                                                                    |
| Function / source references                |        |                                                  |                                                                                    |
| itad-provenance/docs/21 \$5, \$10           |        |                                                  |                                                                                    |
| 13 \$1                                      |        |                                                  |                                                                                    |
| API id                                      | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status                         | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-C6 — Settlement statements

Asset-recovery settlement: proceeds × share – fees, each line tied to a sale event; the statement itself is stamped and verifiable (doc 21 §3).




IT-C6

| Features                     |        |                                                  |                                                                                    |
|------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Summary math.              |        | • Per-item lines referencing sale events.        |                                                                                    |
| • Download + verify.         |        |                                                  |                                                                                    |
| Function / source references |        |                                                  |                                                                                    |
| itad-provenance/docs/21 §3   |        |                                                  |                                                                                    |
| API id                       | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status          | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                 | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                 | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-C7 — Item history — mobile web

IT-C3 reflowed for phones (buyers scanning an asset's QR label).



| IT-C7                        |        |                                |                                                                                    |
|------------------------------|--------|--------------------------------|------------------------------------------------------------------------------------|
| Features                     |        |                                |                                                                                    |
| • Summary badges wrap.       |        | • Single-column history.       |                                                                                    |
| Function / source references |        |                                |                                                                                    |
| itad-provenance/docs/09 §4   |        |                                |                                                                                    |
| API id                       | Method | Path                           | Key params (name:type)                                                             |
| v1.timestamp                 | POST   | customer.verae.ai/v1/timestamp | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-I1 — Field home — iOS

IT-02 with HIG: large title, tab bar, Live Activity for the custody session, and the blue location indicator.



IT-I1

IT-02

| Features                                                                                                               |        |                                                                 |                                                                                    |
|------------------------------------------------------------------------------------------------------------------------|--------|-----------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Status badges; iOS shows the system location indicator + a Live Activity on the Lock Screen during custody sessions. |        | • Large scan button (VisionKit DataScannerViewController).      |                                                                                    |
| • Secondary actions as bordered buttons; no hardware scan key on iPhone (MFi ring scanners optional).                  |        | • Lot context: customer, site, manifest count.                  |                                                                                    |
| • 96 dp scan button + hardware scan key (Zebra DataWedge / Honeywell intents).                                         |        | • Last scanned list with evidence completeness (photos needed). |                                                                                    |
| • Check-in (GPS GeoFix + server time) and Hand off (QR) as large tonal actions.                                        |        | • Live counts and the pickup form's receipt status.             |                                                                                    |
| Function / source references                                                                                           |        |                                                                 |                                                                                    |
| itad-provenance/docs/02 §1                                                                                             |        |                                                                 |                                                                                    |
| 22 §2.1                                                                                                                |        |                                                                 |                                                                                    |
| itad-provenance/docs/22 §4.1                                                                                           |        |                                                                 |                                                                                    |
| 02 §1                                                                                                                  |        |                                                                 |                                                                                    |
| 13 §3–4                                                                                                                |        |                                                                 |                                                                                    |
| API id                                                                                                                 | Method | Path                                                            | Key params (name:type)                                                             |
| v1.timestamp                                                                                                           | POST   | customer.verae.ai/v1/timestamp                                  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

IT-I2 — Scanner — iOS (VisionKit)

IT-03 on iOS: DataScannerViewController with item highlighting; result in a sheet.



| IT-I2                                                                     |        | IT-03                                                                      |                                                                                    |
|---------------------------------------------------------------------------|--------|----------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                  |        |                                                                            |                                                                                    |
| • VisionKit highlights recognised codes/text; tap to choose when several. |        | • Result sheet with HIG buttons; haptic (UINotificationFeedbackGenerator). |                                                                                    |
| • Viewfinder with scan line; works with gloves (no tap needed).           |        | • Supported symbologies; NFC toggle for NTAG labels.                       |                                                                                    |
| • Result sheet: matched manifest line, or 'Not on manifest → Extra'.      |        | • Large next actions; photo hashing on capture.                            |                                                                                    |
| Function / source references                                              |        |                                                                            |                                                                                    |
| itad-provenance/docs/02 §1                                                |        |                                                                            |                                                                                    |
| 22 §2.1                                                                   |        |                                                                            |                                                                                    |
| itad-provenance/docs/02 §1 (Identify)                                     |        |                                                                            |                                                                                    |
| 22 U-i7/U-a2 (no scanner today)                                           |        |                                                                            |                                                                                    |
| API id                                                                    | Method | Path                                                                       | Key params (name:type)                                                             |
| v1.timestamp.status                                                       | GET    | customer.verae.ai/v1/timestamp/status                                      | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                              | POST   | customer.verae.ai/v1/timestamp                                             | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

### IT-I3 — Signature — iOS (PencilKit)

IT-08 on iOS using PencilKit canvas; Apple Pencil on iPad dock tablets.



| IT-I3                                                                         |        | IT-08                                     |                                                                                    |
|-------------------------------------------------------------------------------|--------|-------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                      |        |                                           |                                                                                    |
| • PencilKit canvas; VoiceOver alternative: typed name + Face ID confirmation. |        | • Primary action at bottom per HIG.       |                                                                                    |
| • Plain-language statement of what is accepted.                               |        | • Signature pad with clear; large target. |                                                                                    |
| • Other party's status (signed on their device).                              |        | • Privacy note (doc 07 §4.1 p.staff).     |                                                                                    |
| Function / source references                                                  |        |                                           |                                                                                    |
| itad-provenance/docs/02 §1                                                    |        |                                           |                                                                                    |
| 22 §2.1                                                                       |        |                                           |                                                                                    |
| itad-provenance/docs/07 §4.1                                                  |        |                                           |                                                                                    |
| 13 §4, §11, §17 (signature on phone)                                          |        |                                           |                                                                                    |
| API id                                                                        | Method | Path                                      | Key params (name:type)                                                             |
| v1.timestamp.status                                                           | GET    | customer.verae.ai/v1/timestamp/status     | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                  | POST   | customer.verae.ai/v1/timestamp            | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-I4 — Grading — iOS

IT-09 on iOS: segmented control for functional status; same grade scale.




| IT-I4                                                                         |        | IT-09                                                                 |                                                                                    |
|-------------------------------------------------------------------------------|--------|-----------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                      |        |                                                                       |                                                                                    |
| • Grade buttons ≥ 58 pt.                                                      |        | • UISegmentedControl for functional status.                           |                                                                                    |
| • AI proposal banner with model/version and confidence (DecisionAgent input). |        | • Six large grade targets A+...F with descriptions (not colour only). |                                                                                    |
| • Functional status chips.                                                    |        | • Confirm action names the grade.                                     |                                                                                    |
| Function / source references                                                  |        |                                                                       |                                                                                    |
| itad-provenance/docs/02 §1                                                    |        |                                                                       |                                                                                    |
| 22 §2.1                                                                       |        |                                                                       |                                                                                    |
| itad-provenance/docs/02 §2.2                                                  |        |                                                                       |                                                                                    |
| 13 §6                                                                         |        |                                                                       |                                                                                    |
| API id                                                                        | Method | Path                                                                  | Key params (name:type)                                                             |
| v1.timestamp.status                                                           | GET    | customer.verae.ai/v1/timestamp/status                                 | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                  | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                      | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                  | POST   | customer.verae.ai/v1/timestamp                                        | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-P1 — Partner — shared lots

Downstream processors/buyers see what was shared (Peergos share, DataCube bundle, or report link), redacted (doc 07, 21 §9).



IT-P1

| Features                              |        |                                                  |                                                                                    |
|---------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Share list with channel and expiry. |        | • Redaction/revocation explanation.              |                                                                                    |
| Function / source references          |        |                                                  |                                                                                    |
| itad-provenance/docs/07 §2-6          |        |                                                  |                                                                                    |
| 21 §9                                 |        |                                                  |                                                                                    |
| API id                                | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status                   | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                          | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                          | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-P2 — Partner — accept custody hand-off

A partner accepts a custody transfer as a signed event (doc 21 \$9), with mass-balance check.


web

| IT-P2                                           |        |                                |                                                                                    |
|-------------------------------------------------|--------|--------------------------------|------------------------------------------------------------------------------------|
| Features                                        |        |                                |                                                                                    |
| • Transfer summary with sender's receipt state. |        | • Receiving check fields.      |                                                                                    |
| • Tolerance rule (doc 13 §13 mass balance).     |        |                                |                                                                                    |
| Function / source references                    |        |                                |                                                                                    |
| itad-provenance/docs/21 §9                      |        |                                |                                                                                    |
| 13 §13, §20                                     |        |                                |                                                                                    |
| API id                                          | Method | Path                           | Key params (name:type)                                                             |
| v1.timestamp                                    | POST   | customer.verae.ai/v1/timestamp | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-P3 — Partner — upload evidence

Partners add their own evidence (EP-109), hashed client-side, stamped and linked to shared lots.




IT-P3

| Features                              |              |                                                              |                                                                                                                     |
|---------------------------------------|--------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Drop zone with client-side hashing. |              | • Upload table with receipt states incl. already-registered. |                                                                                                                     |
| Function / source references          |              |                                                              |                                                                                                                     |
| itad-provenance/docs/21 §9 (EP-109)   |              |                                                              |                                                                                                                     |
| API id                                | Method       | Path                                                         | Key params (name:type)                                                                                              |
| v1.timestamp.status                   | GET          | customer.verae.ai/v1/timestamp/status                        | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                       | local + APIs | App add flow (DC-07D)                                        | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                          | —            | peergos.verae.ai (Peergos HTTP/API + local rust)             | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                          | POST         | customer.verae.ai/v1/timestamp                               | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-P4 — Partner — API keys & webhooks

Partner keys scoped to shared lots (authz EP-060) and HMAC-signed webhooks (EP-108).




IT-P4

| Features                     |        |                                                  |                                                                                    |
|------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Scoped keys with revoke.   |        | • Webhooks with event list and health.           |                                                                                    |
| Function / source references |        |                                                  |                                                                                    |
| itad-provenance/docs/21 §9   |        |                                                  |                                                                                    |
| 25 (EP-060, EP-108)          |        |                                                  |                                                                                    |
| API id                       | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status          | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                 | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                 | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-S1 — Station kiosk sign-in (badge + PIN)

Dock-PC kiosk sign-in (U-w6): station has its own device key; operators badge in per shift.




| IT-S1                                                  |        |                                                 |                                                                                    |
|--------------------------------------------------------|--------|-------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                               |        |                                                 |                                                                                    |
| • Station identity + leaf-node health.                 |        | • NFC/HID badge reader; barcode badge fallback. |                                                                                    |
| • PIN (second factor).                                 |        | • Kiosk policy statement.                       |                                                                                    |
| Function / source references                           |        |                                                 |                                                                                    |
| itad-provenance/docs/02 §2 (stations thin, device key) |        |                                                 |                                                                                    |
| 22 U-w6                                                |        |                                                 |                                                                                    |
| API id                                                 | Method | Path                                            | Key params (name:type)                                                             |
| v1.timestamp                                           | POST   | customer.verae.ai/v1/timestamp                  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

### IT-S2 — Dock receipt (shipment level)

Records the truck before any item scan: carrier, BOL/PRO, seals, pallets, weight, hazmat; accept / with exceptions / reject (doc 13 §5).




IT-S2

| Features                                                                     |        |                                                                |                                                                                    |
|------------------------------------------------------------------------------|--------|----------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Projected receipt status (scheduled → arrived → inspecting → accepted...). |        | • Shipment facts grid (scan-to-fill where possible).           |                                                                                    |
| • Seal checks with photos; mismatch → Discrepancy.                           |        | • Documents with receipt states (BOL printed through printit). |                                                                                    |
| • Decision actions; reject sends custody back to carrier.                    |        |                                                                |                                                                                    |
| Function / source references                                                 |        |                                                                |                                                                                    |
| itad-provenance/docs/13 §5                                                   |        |                                                                |                                                                                    |
| 02 §2 (dock receipt)                                                         |        |                                                                |                                                                                    |
| API id                                                                       | Method | Path                                                           | Key params (name:type)                                                             |
| v1.timestamp.status                                                          | GET    | customer.verae.ai/v1/timestamp/status                          | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                 | POST   | customer.verae.ai/v1/timestamp                                 | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

### IT-S3 — Receiving reconciliation vs manifest

Item scans matched to the manifest/ASN with missing / extra / mismatch discrepancies (doc 13 §5, doc 22 §4.2).



IT-S3


IT-SL2

| Features                                                                      |        |                                                                          |                                                                                    |
|-------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Counters with numbers + labels (not colour only).                           |        | • Hardware-scanner input box keeps focus; audible + visual confirmation. |                                                                                    |
| • Result table; each discrepancy becomes a Discrepancy event with resolution. |        | • Close intake gated on final receipts.                                  |                                                                                    |
| • Counters.                                                                   |        | • Scanner entry keeps focus.                                             |                                                                                    |
| Function / source references                                                  |        |                                                                          |                                                                                    |
| itad-provenance/docs/13 §5                                                    |        |                                                                          |                                                                                    |
| 22 §4.2                                                                       |        |                                                                          |                                                                                    |
| API id                                                                        | Method | Path                                                                     | Key params (name:type)                                                             |
| v1.timestamp                                                                  | POST   | customer.verae.ai/v1/timestamp                                           | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-S4 — Supervisor approvals (Mac)

Station-family app on a supervisor's Mac: approve route changes, co-sign verifications, waive close-intake gates.



IT-SM1


IT-S4

| Features                                                          |        |                                                                 |                                                                                                                                    |
|-------------------------------------------------------------------|--------|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Approval queue (Approver / Verifier / Supervisor roles).        |        | • Touch ID signing + separation-of-duties rule.                 |                                                                                                                                    |
| • Component inventory parsed from iDRAC/iLO/lshw/smartctl JSON.   |        | • componentOf explanation; tool output hashed.                  |                                                                                                                                    |
| • Grade with AI proposal confirmation.                            |        | • Route; destroy routes need a human approver (vitad:Approver). |                                                                                                                                    |
| Function / source references                                      |        |                                                                 |                                                                                                                                    |
| itad-provenance/docs/02 §2 (routing approver, supervisor co-sign) |        |                                                                 |                                                                                                                                    |
| 13 §24                                                            |        |                                                                 |                                                                                                                                    |
| itad-provenance/docs/13 §6, §24                                   |        |                                                                 |                                                                                                                                    |
| 02 §2 (audit/test bench)                                          |        |                                                                 |                                                                                                                                    |
| API id                                                            | Method | Path                                                            | Key params (name:type)                                                                                                             |
| sign.requests                                                     | POST   | sign.verae.ai/sign/v1/requests                                  | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| sign.public.sign                                                  | POST   | sign.verae.ai/sign/v1/public/:token/sign                        | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |
| v1.timestamp                                                      | POST   | customer.verae.ai/v1/timestamp                                  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-S5 — Wipe station (per-drive bays)

Drive-bay dashboard: method per NIST/IEEE, progress, pass/fail, separate-operator verification, failed drives routed to destroy (doc 13 §7).



IT-S5


IT-SL1

| Features                                                              |        |                                                                         |                                                                                    |
|-----------------------------------------------------------------------|--------|-------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Bay cards with serial, method/technique, progress and result badge. |        | • Failure handling rule (partial = fail; NAID serial listing).          |                                                                                    |
| • Verification by a different operator (enforced).                    |        | • Log → event explanation.                                              |                                                                                    |
| • AdwBanner (error) for failures.                                     |        | • Boxed list rows per bay; keyboard: arrows + Enter to open bay detail. |                                                                                    |
| Function / source references                                          |        |                                                                         |                                                                                    |
| itad-provenance/docs/13 §7                                            |        |                                                                         |                                                                                    |
| 02 §2 (wipe stations)                                                 |        |                                                                         |                                                                                    |
| API id                                                                | Method | Path                                                                    | Key params (name:type)                                                             |
| v1.timestamp                                                          | POST   | customer.verae.ai/v1/timestamp                                          | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-S6 — Shred / destruction station

Serial-scanned destruction with scale, particle size and CCTV reference; produces the material batch and per-customer Certificates of Destruction (doc 13 §8).




IT-S6

| Features                                 |        |                                                                          |                                                                                    |
|------------------------------------------|--------|--------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Serial log back to each client (NAID). |        | • Stable scale reading via MQTT becomes weightKg on the confirmed event. |                                                                                    |
| • CCTV reference.                        |        | • Start shred = Destruction event (inputs invalidated, batch generated). |                                                                                    |
| Function / source references             |        |                                                                          |                                                                                    |
| itad-provenance/docs/13 §8               |        |                                                                          |                                                                                    |
| 02 §2 (shredder station, MQTT)           |        |                                                                          |                                                                                    |
| API id                                   | Method | Path                                                                     | Key params (name:type)                                                             |
| v1.timestamp                             | POST   | customer.verae.ai/v1/timestamp                                           | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → [VERAE-API-REFERENCE.pdf](#)

IT-S7 — Station offline (leaf buffering)

Station-level offline state: the embedded NATS leaf buffers 7 days; operators see what works and what waits for finality.




| IT-S7                                                    |        | IT-SL3                         |                                                                                    |
|----------------------------------------------------------|--------|--------------------------------|------------------------------------------------------------------------------------|
| Features                                                 |        |                                |                                                                                    |
| • Banner with duration and buffer use.                   |        | • Health tiles.                |                                                                                    |
| • Works / waits list.                                    |        | • AdwStatusPage with counts.   |                                                                                    |
| Function / source references                             |        |                                |                                                                                    |
| itad-provenance/docs/02 §2 (stations thin, 7-day buffer) |        |                                |                                                                                    |
| 03                                                       |        |                                |                                                                                    |
| 11                                                       |        |                                |                                                                                    |
| itad-provenance/docs/02 §2                               |        |                                |                                                                                    |
| API id                                                   | Method | Path                           | Key params (name:type)                                                             |
| v1.timestamp                                             | POST   | customer.verae.ai/v1/timestamp | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-SL1 — Wipe station (per-drive bays)

Drive-bay dashboard: method per NIST/IEEE, progress, pass/fail, separate-operator verification, failed drives routed to destroy (doc 13 §7).




| IT-S5                                                                 |        | IT-SL1                                                                  |                                                                                    |
|-----------------------------------------------------------------------|--------|-------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                              |        |                                                                         |                                                                                    |
| • Bay cards with serial, method/technique, progress and result badge. |        | • Failure handling rule (partial = fail; NAID serial listing).          |                                                                                    |
| • Verification by a different operator (enforced).                    |        | • Log → event explanation.                                              |                                                                                    |
| • AdwBanner (error) for failures.                                     |        | • Boxed list rows per bay; keyboard: arrows + Enter to open bay detail. |                                                                                    |
| Function / source references                                          |        |                                                                         |                                                                                    |
| itad-provenance/docs/13 §7                                            |        |                                                                         |                                                                                    |
| 02 §2 (wipe stations)                                                 |        |                                                                         |                                                                                    |
| API id                                                                | Method | Path                                                                    | Key params (name:type)                                                             |
| v1.timestamp                                                          | POST   | customer.verae.ai/v1/timestamp                                          | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-SL2 — Receiving reconciliation vs manifest

Item scans matched to the manifest/ASN with missing / extra / mismatch discrepancies (doc 13 §5, doc 22 §4.2).




| Features                                                                      |        |                                                                          |                                                                                    |
|-------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Counters with numbers + labels (not colour only).                           |        | • Hardware-scanner input box keeps focus; audible + visual confirmation. |                                                                                    |
| • Result table; each discrepancy becomes a Discrepancy event with resolution. |        | • Close intake gated on final receipts.                                  |                                                                                    |
| • Counters.                                                                   |        | • Scanner entry keeps focus.                                             |                                                                                    |
| Function / source references                                                  |        |                                                                          |                                                                                    |
| itad-provenance/docs/13 §5                                                    |        |                                                                          |                                                                                    |
| 22 §4.2                                                                       |        |                                                                          |                                                                                    |
| API id                                                                        | Method | Path                                                                     | Key params (name:type)                                                             |
| v1.timestamp                                                                  | POST   | customer.verae.ai/v1/timestamp                                           | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-SL3 — Station offline (leaf buffering)

Station-level offline state: the embedded NATS leaf buffers 7 days; operators see what works and what waits for finality.




| Features                                                 |        |                                |                                                                                    |
|----------------------------------------------------------|--------|--------------------------------|------------------------------------------------------------------------------------|
| • Banner with duration and buffer use.                   |        | • Health tiles.                |                                                                                    |
| • Works / waits list.                                    |        | • AdwStatusPage with counts.   |                                                                                    |
| Function / source references                             |        |                                |                                                                                    |
| itad-provenance/docs/02 §2 (stations thin, 7-day buffer) |        |                                |                                                                                    |
| 03                                                       |        |                                |                                                                                    |
| 11                                                       |        |                                |                                                                                    |
| itad-provenance/docs/02 §2                               |        |                                |                                                                                    |
| API id                                                   | Method | Path                           | Key params (name:type)                                                             |
| v1.timestamp                                             | POST   | customer.verae.ai/v1/timestamp | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-SM1 — Supervisor approvals (Mac)

Station-family app on a supervisor's Mac: approve route changes, co-sign verifications, waive close-intake gates.



IT-SM1


IT-S4

| Features                                                          |        |                                                                 |                                                                                                                                    |
|-------------------------------------------------------------------|--------|-----------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Approval queue (Approver / Verifier / Supervisor roles).        |        | • Touch ID signing + separation-of-duties rule.                 |                                                                                                                                    |
| • Component inventory parsed from iDRAC/iLO/lshw/smartctl JSON.   |        | • componentOf explanation; tool output hashed.                  |                                                                                                                                    |
| • Grade with AI proposal confirmation.                            |        | • Route; destroy routes need a human approver (vitad:Approver). |                                                                                                                                    |
| Function / source references                                      |        |                                                                 |                                                                                                                                    |
| itad-provenance/docs/02 §2 (routing approver, supervisor co-sign) |        |                                                                 |                                                                                                                                    |
| 13 §24                                                            |        |                                                                 |                                                                                                                                    |
| itad-provenance/docs/13 §6, §24                                   |        |                                                                 |                                                                                                                                    |
| 02 §2 (audit/test bench)                                          |        |                                                                 |                                                                                                                                    |
| API id                                                            | Method | Path                                                            | Key params (name:type)                                                                                                             |
| sign.requests                                                     | POST   | sign.verae.ai/sign/v1/requests                                  | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| sign.public.sign                                                  | POST   | sign.verae.ai/sign/v1/public/:token/sign                        | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |
| v1.timestamp                                                      | POST   | customer.verae.ai/v1/timestamp                                  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |

Sample calls + full param tables → VERÆ-API-REFERENCE.pdf

IT-W1 — Ops console — floor & dock dashboard

Operations overview: lots in progress, items by stage, docks, exceptions, pending-receipt depth and finality lag (doc 21 §7).




IT-W1

| Features                                                                        |              |                                                  |                                                                                                                     |
|---------------------------------------------------------------------------------|--------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • KPIs incl. pending receipts and finality lag vs the p95 22 s target (doc 24). |              | • Items by stage bars (with numbers).            |                                                                                                                     |
| • Dock door status.                                                             |              | • Exceptions list with case action.              |                                                                                                                     |
| Function / source references                                                    |              |                                                  |                                                                                                                     |
| itad-provenance/docs/21 §7                                                      |              |                                                  |                                                                                                                     |
| 24                                                                              |              |                                                  |                                                                                                                     |
| 13 §22                                                                          |              |                                                  |                                                                                                                     |
| API id                                                                          | Method       | Path                                             | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                             | GET          | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                                 | local + APIs | App add flow (DC-07D)                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                                    | —            | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                    | POST         | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

IT-W2 — Lot detail — timeline & evidence

One lot: lifecycle stage, event timeline with per-event receipt states, evidence progress and items.




IT-W2

| Features                                                                     |              |                                                  |                                                                                                                     |
|------------------------------------------------------------------------------|--------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Lifecycle stage chips (Intake → Triage → Process → Dispose → Certificate). |              | • Timeline with Substrate state per event.       |                                                                                                                     |
| • Evidence progress and lot-cube status.                                     |              | • Items list → item history.                     |                                                                                                                     |
| Function / source references                                                 |              |                                                  |                                                                                                                     |
| itad-provenance/docs/13                                                      |              |                                                  |                                                                                                                     |
| 06                                                                           |              |                                                  |                                                                                                                     |
| 17                                                                           |              |                                                  |                                                                                                                     |
| API id                                                                       | Method       | Path                                             | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                          | GET          | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                              | local + APIs | App add flow (DC-07D)                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                                 | —            | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                                 | POST         | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-W3 — Pending-receipt queue & chain status

Queue depth and age by stage, chain health (finality lag), hardening warning, and per-digest reconcile (never blind resubmit).




IT-W3

| Features                                                                  |              |                                                                            |                                                                                                                     |
|---------------------------------------------------------------------------|--------------|----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Stage counters with latency percentiles (doc 24 targets are estimates). |              | • Chain status (best vs finalized block) + hardening warning (doc 16 §11). |                                                                                                                     |
| • Per-digest table; Reconcile runs lookup-by-digest.                      |              |                                                                            |                                                                                                                     |
| Function / source references                                              |              |                                                                            |                                                                                                                     |
| itad-provenance/docs/24                                                   |              |                                                                            |                                                                                                                     |
| 16 §6, §11                                                                |              |                                                                            |                                                                                                                     |
| 21 §7                                                                     |              |                                                                            |                                                                                                                     |
| API id                                                                    | Method       | Path                                                                       | Key params (name:type)                                                                                              |
| v1.timestamp.status                                                       | GET          | customer.verae.ai/v1/timestamp/status                                      | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                                           | local + APIs | App add flow (DC-07D)                                                      | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                              | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                           | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                              | POST         | customer.verae.ai/v1/timestamp                                             | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## IT-W4 — Pickups — schedule & assign trucks

Schedule pickups, assign trucks/drivers, and process requests from the customer portal (doc 21 §7, 13 §1).




IT-W4

| Features                                      |        |                                                 |                                                                                                                                    |
|-----------------------------------------------|--------|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Calendar cards per day with truck + driver. |        | • Inbound requests (EP-110) with assign action. |                                                                                                                                    |
| Function / source references                  |        |                                                 |                                                                                                                                    |
| itad-provenance/docs/13 §1                    |        |                                                 |                                                                                                                                    |
| 21 §5, §7                                     |        |                                                 |                                                                                                                                    |
| API id                                        | Method | Path                                            | Key params (name:type)                                                                                                             |
| sign.requests                                 | POST   | sign.verae.ai/sign/v1/requests                  | documentSha256:string 64 hex, documentName:string, signers:array<(email:string,name?:string)>, title:string?, message:string?, ... |
| sign.public.sign                              | POST   | sign.verae.ai/sign/v1/public/:token/sign        | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |
| v1.timestamp                                  | POST   | customer.verae.ai/v1/timestamp                  | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

## IT-W5 — Exceptions & cases

Custody gaps, seal mismatches, discrepancies: evidence and an append-only resolution (corrections are new events).




IT-W5

| Features                                       |        |                                |                                                                                    |
|------------------------------------------------|--------|--------------------------------|------------------------------------------------------------------------------------|
| • Narrative + map of the gap.                  |        | • Evidence events with states. |                                                                                    |
| • Resolution options; recorded as a new event. |        |                                |                                                                                    |
| Function / source references                   |        |                                |                                                                                    |
| itad-provenance/docs/13 §4, §18                |        |                                |                                                                                    |
| 21 §4                                          |        |                                |                                                                                    |
| API id                                         | Method | Path                           | Key params (name:type)                                                             |
| v1.timestamp                                   | POST   | customer.verae.ai/v1/timestamp | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

IT-W6 — Certificate lifecycle

Draft → pending signatures → issued → revoked / superseded / expired; each signature and the issue are stamped (doc 13 §23, 15 §5).




IT-W6

| Features                                                                           |        |                                                    |                                                                                    |
|------------------------------------------------------------------------------------|--------|----------------------------------------------------|------------------------------------------------------------------------------------|
| • Certificate register with lifecycle and receipt state; revoke needs cert.revoke. |        | • Signature progress (via the signing round-trip). |                                                                                    |
| Function / source references                                                       |        |                                                    |                                                                                    |
| itad-provenance/docs/13 §23                                                        |        |                                                    |                                                                                    |
| 15 §5                                                                              |        |                                                    |                                                                                    |
| API id                                                                             | Method | Path                                               | Key params (name:type)                                                             |
| v1.timestamp.status                                                                | GET    | customer.verae.ai/v1/timestamp/status              | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                       | POST   | customer.verae.ai/v1/timestamp                     | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## MT-M1 — Verae Timestamping (Mac) — drop, hash, receipts

Redesign of the existing SwiftUI app (ContentView.swift: drop files, Register/Verify, receipt list, export). Adds Substrate receipt states and the metered route.




MT-M1

| Features                                                                                                                     |              |                                                                                |                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------------|--------------|--------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Drop zone + paste-a-hash; bare digest treated as SHA-256.                                                                  |              | • Receipt table with the 4-state model (replaces register/verify result text). |                                                                                                                                    |
| • Route change note (MCP → metered zap).                                                                                     |              |                                                                                |                                                                                                                                    |
| Function / source references                                                                                                 |              |                                                                                |                                                                                                                                    |
| verae-mcp-timestamping-client/mac/VeraeTimestamping/ContentView.swift, MCPClient.swift, FileHasher.swift, ReceiptStore.swift |              |                                                                                |                                                                                                                                    |
| API id                                                                                                                       | Method       | Path                                                                           | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                                                                                          | GET          | customer.verae.ai/v1/timestamp/status                                          | sha256:string (64 hex), jobId:string?                                                                                              |
| peergos.cube                                                                                                                 | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                               | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                                                                                                | POST         | sign.verae.ai/sign/v1/requests                                                 | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                                                                                                 | POST         | customer.verae.ai/v1/timestamp                                                 | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |
| add.destination                                                                                                              | local + APIs | App add flow (DC-07D)                                                          | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadata.Jsonl:string (JSONL), ...               |
| sign.public.sign                                                                                                             | POST         | sign.verae.ai/sign/v1/public/:token/sign                                       | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## MT-M2 — Export sheet with not-final guard

ExportPDF.swift redesign: certificates are issued only for final receipts; non-final ones export as clearly-marked drafts.




MT-M2

| Features                                      |        |                                                                |                                                                                    |
|-----------------------------------------------|--------|----------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Format choice (existing JSON/CSV/Text/PDF). |        | • Guard against presenting non-final receipts as certificates. |                                                                                    |
| Function / source references                  |        |                                                                |                                                                                    |
| ExportPDF.swift                               |        |                                                                |                                                                                    |
| ContentView.swift exportResults               |        |                                                                |                                                                                    |
| API id                                        | Method | Path                                                           | Key params (name:type)                                                             |
| v1.timestamp.status                           | GET    | customer.verae.ai/v1/timestamp/status                          | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                  | POST   | customer.verae.ai/v1/timestamp                                 | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

PT-01 — Print dialog → “Verae Timestamping” printer

Entry point: the user prints from any app and picks the Verae Timestamping printer (CUPS backend / IPP). The dialog explains what happens.



PT-01

PT-W1


PT-L1

| Features                                                                                                                       |        |                                                                                                                                                                |                                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Printer named 'Verae Timestamping' (macOS CUPS/IPP queue installed by the .pkg).                                             |        | • Proposed: printer-info / PPD description text so the system dialog shows what the printer does and who is signed in (via the printer's location/info field). |                                                                                    |
| • Printer installed by install-printer.ps1 (IPP Class Driver).                                                                 |        | • Printer comment/location text explains behaviour.                                                                                                            |                                                                                    |
| • CUPS queue with descriptive printer-info.                                                                                    |        | • Output location shown.                                                                                                                                       |                                                                                    |
| Function / source references                                                                                                   |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/macos/cups/backend-verae.sh, platform/macos/ipp/install-ipp-printer.sh, cmd/verae-print/main.go |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/windows/scripts/install-printer.ps1                                                             |        |                                                                                                                                                                |                                                                                    |
| internal/winprint/ipp.go, watch.go                                                                                             |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/linux/cups/backend-verae.sh                                                                     |        |                                                                                                                                                                |                                                                                    |
| platform/linux/deb/build-deb.sh                                                                                                |        |                                                                                                                                                                |                                                                                    |
| API id                                                                                                                         | Method | Path                                                                                                                                                           | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                                            | GET    | customer.verae.ai/v1/timestamp/status                                                                                                                          | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                                                                   | POST   | customer.verae.ai/v1/timestamp                                                                                                                                 | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

PT-02 — Sign-in prompt — choose how to connect

Native SwiftUI window replacing the chain of AppleScript dialogs in keyflow\_gui.go. Same options, one window, keyboard-navigable.



PT-02

PT-W2

PT-L2

| Features                                                                                                               |                 |                                                                                               |                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Why this appears, in one sentence (existing intro copy).                                                             |                 | • The five existing options as a radio card list (Keep existing key appears when one exists). |                                                                                                                                    |
| • Where the key is stored (Keychain + ~/.verae today).                                                                 |                 | • SelectorBar tabs replace the option list.                                                   |                                                                                                                                    |
| • 2FA field appears when required.                                                                                     |                 | • Storage note (user-token.ps1 / DPAPI).                                                      |                                                                                                                                    |
| • AdwDialog with AdwEntryRow / AdwPasswordEntryRow.                                                                    |                 | • 2FA row appears when needed.                                                                |                                                                                                                                    |
| • Paste key / reset as secondary links.                                                                                |                 |                                                                                               |                                                                                                                                    |
| Function / source references                                                                                           |                 |                                                                                               |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keyflow_gui.go (optKeep/optLogin/optCreate/optPaste/optSkip), keysetup_darwin.go |                 |                                                                                               |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keydialog_windows.go                                                             |                 |                                                                                               |                                                                                                                                    |
| platform/windows/scripts/user-token.ps1                                                                                |                 |                                                                                               |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keyflow_gui.go (zenity), keysetup_linux.go                                       |                 |                                                                                               |                                                                                                                                    |
| API id                                                                                                                 | Method          | Path                                                                                          | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                                                                                    | GET             | customer.verae.ai/v1/timestamp/status                                                         | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                                                                                           | —               | peergos.verae.ai (Peergos HTTP/API + local rust)                                              | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                                                                                          | POST            | sign.verae.ai/sign/v1/requests                                                                | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                                                                                           | POST            | customer.verae.ai/v1/timestamp                                                                | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| portal.login                                                                                                           | POST            | customer.verae.ai/portal/api/login                                                            | email:string, password:string, totpCode:string (6 digits)                                                                          |
| portal.2fa                                                                                                             | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*                                                            | setup:POST {}, code:string, totpCode:string                                                                                        |
| sign.public.sign                                                                                                       | POST            | sign.verae.ai/sign/v1/public/:token/sign                                                      | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

PT-03 — Sign in · 2FA · password reset

The sign-in sequence (email → password → 2FA) and in-app password reset (v0.3.4) as steps in one window.




| PT-03                                                                                                          |                 |                                            |                                                                                                                                    |
|----------------------------------------------------------------------------------------------------------------|-----------------|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Features                                                                                                       |                 |                                            |                                                                                                                                    |
| • Stepper replaces separate modal dialogs.                                                                     |                 | • Segmented 6-digit code; paste fills all. |                                                                                                                                    |
| • Forgot password → emailed code reset (variant).                                                              |                 |                                            |                                                                                                                                    |
| Function / source references                                                                                   |                 |                                            |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keyflow_gui.go (sign in, 2FA, reset flow), internal/auth/portal_reset.go |                 |                                            |                                                                                                                                    |
| API id                                                                                                         | Method          | Path                                       | Key params (name:type)                                                                                                             |
| sign.requests                                                                                                  | POST            | sign.verae.ai/sign/v1/requests             | documentSha256:string 64 hex, documentName:string, signers:array<(email:string,name?:string)>, title:string?, message:string?, ... |
| v1.timestamp                                                                                                   | POST            | customer.verae.ai/v1/timestamp             | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| portal.login                                                                                                   | POST            | customer.verae.ai/portal/api/login         | email:string, password:string, totpCode:string (6 digits)                                                                          |
| portal.2fa                                                                                                     | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*         | setup:POST {}, code:string, totpCode:string                                                                                        |
| sign.public.sign                                                                                               | POST            | sign.verae.ai/sign/v1/public/:token/sign   | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

PT-04 — Print job queue + receipt status

New window listing every printed job with its receipt state — today success/pending are only visible as files appearing in a folder (U-w3).



PT-04

PT-W4

PT-L3

| Features                                                                                                                                                                                                                                                                                                      |        |                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                    |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>Held-job banner: 401/403 jobs are kept in the pending folder and retried after a new key (pending.go).</li> <li>Detail: state, multihash, timeline, output files; certificate only after final; never uses the local clock (PR1).</li> <li>Held-job banner.</li> </ul> |        | <ul style="list-style-type: none"> <li>Job table: document, source app, multihash, receipt state. A pending zap response is held as 'Pending receipt' — never failed and never shown as a jobId (PR2).</li> <li>InfoBar for held jobs; same table/detail components; settings page mirrors PT-07 (route, output folder, Signed/).</li> <li>Notification on final / held with actions.</li> </ul> |                                                                                    |
|                                                                                                                                                                                                                                                                                                               |        | Function / source references                                                                                                                                                                                                                                                                                                                                                                     |                                                                                    |
|                                                                                                                                                                                                                                                                                                               |        | PrintToVeraeTimeStamp/cmd/verae-print/pending.go, stampcore.go, serve.go<br>internal/job/job.go<br>internal/veraeapi/client.go<br>PrintToVeraeTimeStamp/internal/job/job.go<br>PrintToVeraeTimeStamp/platform/Linux/README.txt                                                                                                                                                                   |                                                                                    |
| API id                                                                                                                                                                                                                                                                                                        | Method | Path                                                                                                                                                                                                                                                                                                                                                                                             | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                                                                                                                                                                                                                           | GET    | customer.verae.ai/v1/timestamp/status                                                                                                                                                                                                                                                                                                                                                            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                                                                                                                                                                                                                                                  | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                                                                                                                                                                                                                                                                                                                                                 | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                                                                                                                                                                                                                                                  | POST   | customer.verae.ai/v1/timestamp                                                                                                                                                                                                                                                                                                                                                                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

PT-05 — Final receipt + certificate ready

Job detail in the final state: proof summary, verify link and QR. and the certificate.




PT-05

| Features                                                                                  |        |                                                                                |                                                                                    |
|-------------------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Final state with green banner.                                                          |        | • Proof: chain, block, extrinsic, GRANDPA finality, Merkle proof, server time. |                                                                                    |
| • Verify link + QR (same as certificate).                                                 |        |                                                                                |                                                                                    |
| Function / source references                                                              |        |                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/internal/pdfcert/pdfcert.go (QR LookupURL → explorer.verae.ai/time) |        |                                                                                |                                                                                    |
| API id                                                                                    | Method | Path                                                                           | Key params (name:type)                                                             |
| v1.timestamp.status                                                                       | GET    | customer.verae.ai/v1/timestamp/status                                          | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                              | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                               | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                              | POST   | customer.verae.ai/v1/timestamp                                                 | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

PT-06 — Menu bar status + notifications (Mac)

Ambient job status after printing: menu bar extra with waiting/held jobs; notifications for 'certificate ready' and 'held'.




| PT-06                                                                                |        | PT-W3                                                                               |                                                                                    |
|--------------------------------------------------------------------------------------|--------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| Features                                                                             |        |                                                                                     |                                                                                    |
| • Menu bar extra: waiting / held jobs with stage text.                               |        | • Notification when final (certificate ready) and when held (sign in).              |                                                                                    |
| • Tray flyout: printer health + recent jobs with state badges.                       |        | • Toast for held job with Sign in action (also 'Certificate ready' toast on final). |                                                                                    |
| Function / source references                                                         |        |                                                                                     |                                                                                    |
| New (PR3)                                                                            |        |                                                                                     |                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/serve.go, hide_windows.go, platform_windows.go |        |                                                                                     |                                                                                    |
| lib/files/file_browser.dart                                                          |        |                                                                                     |                                                                                    |
| lib/timestamps/auto_stamp.dart                                                       |        |                                                                                     |                                                                                    |
| API id                                                                               | Method | Path                                                                                | Key params (name:type)                                                             |
| peergos.cube                                                                         | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                                    | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                         | POST   | customer.verae.ai/v1/timestamp                                                      | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

PT-07 — Settings (Mac)

One settings window replacing scattered config: account/key, route, output folder, certificate and notification options, Signed/ folder subscription (doc 23 ES4).




PT-07

| Features                                                  |        |                                                                                                             |                                                                                    |
|-----------------------------------------------------------|--------|-------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Account + key (masked) with replace.                    |        | • Route defaults to zap (metered); the macOS CUPS script's legacy 'verae' default is removed (doc 22 §2.5). |                                                                                    |
| • Signed/ folder subscription for the signing round-trip. |        |                                                                                                             |                                                                                    |
| Function / source references                              |        |                                                                                                             |                                                                                    |
| PrintToVeraeTimeStamp/internal/settings/settings.go       |        |                                                                                                             |                                                                                    |
| platform/macos/cups/backend-verae.sh (channel default)    |        |                                                                                                             |                                                                                    |
| lib/files/file_browser.dart                               |        |                                                                                                             |                                                                                    |
| lib/timestamps/auto_stamp.dart                            |        |                                                                                                             |                                                                                    |
| API id                                                    | Method | Path                                                                                                        | Key params (name:type)                                                             |
| v1.timestamp.status                                       | GET    | customer.verae.ai/v1/timestamp/status                                                                       | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                              | POST   | customer.verae.ai/v1/timestamp                                                                              | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

PT-08 — Offline & server-error states (printit)

Shows queued stamps offline and the 'time not confirmed' error that replaces today's local-clock fallback (U-w2/PR1).




PT-08

| Features                                                                                |        |                                                                                  |                                                                                    |
|-----------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Offline banner; PDFs still written, stamps queued.                                    |        | • Server omitted time → no certificate, reconcile by digest (never local clock). |                                                                                    |
| Function / source references                                                            |        |                                                                                  |                                                                                    |
| PrintToVeraeTimeStamp/internal/veraeapi/client.go (≈330 local-clock fallback – removed) |        |                                                                                  |                                                                                    |
| API id                                                                                  | Method | Path                                                                             | Key params (name:type)                                                             |
| v1.timestamp.status                                                                     | GET    | customer.verae.ai/v1/timestamp/status                                            | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                            | POST   | customer.verae.ai/v1/timestamp                                                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## PT-A1 — Android PrintService “Verae Timestamping” (proposal)

Android supports print-service plugins, so a true 'print to Verae' is possible: the Verae app registers a PrintService that appears in the system print dialog.




PT-A1

| Features                                                                  |        |                                       |                                                                                    |
|---------------------------------------------------------------------------|--------|---------------------------------------|------------------------------------------------------------------------------------|
| • Verae Timestamping as a printer in the Android print UI (PrintService). |        | • Explains where results appear.      |                                                                                    |
| Function / source references                                              |        |                                       |                                                                                    |
| New                                                                       |        |                                       |                                                                                    |
| API id                                                                    | Method | Path                                  | Key params (name:type)                                                             |
| v1.timestamp.status                                                       | GET    | customer.verae.ai/v1/timestamp/status | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                              | POST   | customer.verae.ai/v1/timestamp        | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

PT-B1 — printit.verae.ai — download & how it works

Refresh of the existing dark site: OS-detected download, a 4-step explainer that uses the final-receipt language, and a verify entry.




PT-B1

| Features                                                                                                    |        |                                                          |                                                                                    |
|-------------------------------------------------------------------------------------------------------------|--------|----------------------------------------------------------|------------------------------------------------------------------------------------|
| • Hero copy: certificate + QR + final on Substrate.                                                         |        | • OS-detected primary download; other platforms visible. |                                                                                    |
| • 4-step explainer.                                                                                         |        | • Verify entry → ZP-V1.                                  |                                                                                    |
| Function / source references                                                                                |        |                                                          |                                                                                    |
| PrintToVeraeTimeStamp/site/printit.verae.ai/index.html (palette var(--night) / var(--gold) / var(--violet)) |        |                                                          |                                                                                    |
| API id                                                                                                      | Method | Path                                                     | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                         | GET    | customer.verae.ai/v1/timestamp/status                    | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                                                | —      | peergos.verae.ai (Peergos HTTP/API + local rust)         | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                                                | POST   | customer.verae.ai/v1/timestamp                           | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

PT-11 — iOS share extension “Timestamp with Verae” (proposal)

printit has no mobile client. iOS cannot add virtual printers, so the equivalent is a share/action extension (from Mail, Files, Print preview ■ Share) that hashes and stamps.




PT-11

| Features                                                    |              |                                                                       |                                                                                                                     |
|-------------------------------------------------------------|--------------|-----------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Extension shows the file and computes the hash on device. |              | • Pending state + where the certificate will land; finality via push. |                                                                                                                     |
| Function / source references                                |              |                                                                       |                                                                                                                     |
| New (ES4 / doc 22 'no mobile')                              |              |                                                                       |                                                                                                                     |
| API id                                                      | Method       | Path                                                                  | Key params (name:type)                                                                                              |
| v1.timestamp.status                                         | GET          | customer.verae.ai/v1/timestamp/status                                 | sha256:string (64 hex), jobId:string?                                                                               |
| add.destination                                             | local + APIs | App add flow (DC-07D)                                                 | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ... |
| peergos.cube                                                | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                      | username:string, password:string, path:string, bytes:bytes                                                          |
| v1.timestamp                                                | POST         | customer.verae.ai/v1/timestamp                                        | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                  |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

PT-L1 — Print dialog → “Verae Timestamping” printer

Entry point: the user prints from any app and picks the Verae Timestamping printer (CUPS backend / IPP). The dialog explains what happens.



PT-01

PT-W1


PT-L1

| Features                                                                                                                       |        |                                                                                                                                                                |                                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Printer named 'Verae Timestamping' (macOS CUPS/IPP queue installed by the .pkg).                                             |        | • Proposed: printer-info / PPD description text so the system dialog shows what the printer does and who is signed in (via the printer's location/info field). |                                                                                    |
| • Printer installed by install-printer.ps1 (IPP Class Driver).                                                                 |        | • Printer comment/location text explains behaviour.                                                                                                            |                                                                                    |
| • CUPS queue with descriptive printer-info.                                                                                    |        | • Output location shown.                                                                                                                                       |                                                                                    |
| Function / source references                                                                                                   |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/macos/cups/backend-verae.sh, platform/macos/ipp/install-ipp-printer.sh, cmd/verae-print/main.go |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/windows/scripts/install-printer.ps1                                                             |        |                                                                                                                                                                |                                                                                    |
| internal/winprint/ipp.go, watch.go                                                                                             |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/linux/cups/backend-verae.sh                                                                     |        |                                                                                                                                                                |                                                                                    |
| platform/linux/deb/build-deb.sh                                                                                                |        |                                                                                                                                                                |                                                                                    |
| API id                                                                                                                         | Method | Path                                                                                                                                                           | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                                            | GET    | customer.verae.ai/v1/timestamp/status                                                                                                                          | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                                                                   | POST   | customer.verae.ai/v1/timestamp                                                                                                                                 | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERA-REFERENCE.pdf

PT-L2 — Sign-in prompt — choose how to connect

Native SwiftUI window replacing the chain of AppleScript dialogs in keyflow\_gui.go. Same options, one window, keyboard-navigable.



PT-02

PT-W2


PT-L2

| Features                                                                                                               |                 |                                                                                               |                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------|-----------------|-----------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Why this appears, in one sentence (existing intro copy).                                                             |                 | • The five existing options as a radio card list (Keep existing key appears when one exists). |                                                                                                                                    |
| • Where the key is stored (Keychain + ~/.verae today).                                                                 |                 | • SelectorBar tabs replace the option list.                                                   |                                                                                                                                    |
| • 2FA field appears when required.                                                                                     |                 | • Storage note (user-token.ps1 / DPAPI).                                                      |                                                                                                                                    |
| • AdwDialog with AdwEntryRow / AdwPasswordEntryRow.                                                                    |                 | • 2FA row appears when needed.                                                                |                                                                                                                                    |
| • Paste key / reset as secondary links.                                                                                |                 |                                                                                               |                                                                                                                                    |
| Function / source references                                                                                           |                 |                                                                                               |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keyflow_gui.go (optKeep/optLogin/optCreate/optPaste/optSkip), keysetup_darwin.go |                 |                                                                                               |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keydialog_windows.go                                                             |                 |                                                                                               |                                                                                                                                    |
| platform/windows/scripts/user-token.ps1                                                                                |                 |                                                                                               |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keyflow_gui.go (zenity), keysetup_linux.go                                       |                 |                                                                                               |                                                                                                                                    |
| API id                                                                                                                 | Method          | Path                                                                                          | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                                                                                    | GET             | customer.verae.ai/v1/timestamp/status                                                         | sha256:string (64 hex), jobId:string?                                                                                              |
| peergos.cube                                                                                                           | —               | peergos.verae.ai (Peergos HTTP/API + local rust)                                              | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                                                                                          | POST            | sign.verae.ai/sign/v1/requests                                                                | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                                                                                           | POST            | customer.verae.ai/v1/timestamp                                                                | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |
| portal.login                                                                                                           | POST            | customer.verae.ai/portal/api/login                                                            | email:string, password:string, totpCode:string (6 digits)                                                                          |
| portal.2fa                                                                                                             | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*                                                            | setup:POST {}, code:string, totpCode:string                                                                                        |
| sign.public.sign                                                                                                       | POST            | sign.verae.ai/sign/v1/public/:token/sign                                                      | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

PT-L3 — Print job queue + receipt status

New window listing every printed job with its receipt state — today success/pending are only visible as files appearing in a folder (U-w3).



PT-04

PT-W4


PT-L3

| Features                                                                                                                                                                                                                                                                                                        |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>• Held-job banner: 401/403 jobs are kept in the pending folder and retried after a new key (pending.go).</li><li>• Detail: state, multihash, timeline, output files; certificate only after final; never uses the local clock (PR1).</li><li>• Held-job banner.</li></ul> |        | <ul style="list-style-type: none"><li>• Job table: document, source app, multihash, receipt state. A pending zap response is held as 'Pending receipt' — never failed and never shown as a jobId (PR2).</li><li>• InfoBar for held jobs; same table/detail components; settings page mirrors PT-07 (route, output folder, Signed/).</li><li>• Notification on final / held with actions.</li></ul> |                                                                                    |
| Function / source references                                                                                                                                                                                                                                                                                    |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/pending.go, stampcore.go, serve.go                                                                                                                                                                                                                                        |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| internal/job/job.go                                                                                                                                                                                                                                                                                             |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| internal/veraeapi/client.go                                                                                                                                                                                                                                                                                     |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| PrintToVeraeTimeStamp/internal/job/job.go                                                                                                                                                                                                                                                                       |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| PrintToVeraeTimeStamp/platform/linux/README.txt                                                                                                                                                                                                                                                                 |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| API id                                                                                                                                                                                                                                                                                                          | Method | Path                                                                                                                                                                                                                                                                                                                                                                                               | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                                                                                                                                                                                                                             | GET    | customer.verae.ai/v1/timestamp/status                                                                                                                                                                                                                                                                                                                                                              | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                                                                                                                                                                                                                                                    | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                                                                                                                                                                                                                                                                                                                                                   | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                                                                                                                                                                                                                                                    | POST   | customer.verae.ai/v1/timestamp                                                                                                                                                                                                                                                                                                                                                                     | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERA-API-REFERENCE.pdf

PT-W1 — Print dialog → “Verae Timestamping” printer

Entry point: the user prints from any app and picks the Verae Timestamping printer (CUPS backend / IPP). The dialog explains what happens.



PT-01

PT-W1


PT-L1

| Features                                                                                                                       |        |                                                                                                                                                                |                                                                                    |
|--------------------------------------------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Printer named 'Verae Timestamping' (macOS CUPS/IPP queue installed by the .pkg).                                             |        | • Proposed: printer-info / PPD description text so the system dialog shows what the printer does and who is signed in (via the printer's location/info field). |                                                                                    |
| • Printer installed by install-printer.ps1 (IPP Class Driver).                                                                 |        | • Printer comment/location text explains behaviour.                                                                                                            |                                                                                    |
| • CUPS queue with descriptive printer-info.                                                                                    |        | • Output location shown.                                                                                                                                       |                                                                                    |
| Function / source references                                                                                                   |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/macos/cups/backend-verae.sh, platform/macos/ipp/install-ipp-printer.sh, cmd/verae-print/main.go |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/windows/scripts/install-printer.ps1                                                             |        |                                                                                                                                                                |                                                                                    |
| internal/winprint/ipp.go, watch.go                                                                                             |        |                                                                                                                                                                |                                                                                    |
| PrintToVeraeTimeStamp/platform/linux/cups/backend-verae.sh                                                                     |        |                                                                                                                                                                |                                                                                    |
| platform/linux/deb/build-deb.sh                                                                                                |        |                                                                                                                                                                |                                                                                    |
| API id                                                                                                                         | Method | Path                                                                                                                                                           | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                                            | GET    | customer.verae.ai/v1/timestamp/status                                                                                                                          | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                                                                                                                   | POST   | customer.verae.ai/v1/timestamp                                                                                                                                 | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERA-REFERENCE.pdf

PT-W2 — Sign-in prompt — choose how to connect

Native SwiftUI window replacing the chain of AppleScript dialogs in keyflow\_gui.go. Same options, one window, keyboard-navigable.




| PT-02                                                                                                                  | PT-W2                                                                                         | PT-L2                                            |                                                                                                                                    |
|------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Features                                                                                                               |                                                                                               |                                                  |                                                                                                                                    |
| • Why this appears, in one sentence (existing intro copy).                                                             | • The five existing options as a radio card list (Keep existing key appears when one exists). |                                                  |                                                                                                                                    |
| • Where the key is stored (Keychain + ~/.verae today).                                                                 | • SelectorBar tabs replace the option list.                                                   |                                                  |                                                                                                                                    |
| • 2FA field appears when required.                                                                                     | • Storage note (user-token.ps1 / DPAPI).                                                      |                                                  |                                                                                                                                    |
| • AdwDialog with AdwEntryRow / AdwPasswordEntryRow.                                                                    | • 2FA row appears when needed.                                                                |                                                  |                                                                                                                                    |
| • Paste key / reset as secondary links.                                                                                |                                                                                               |                                                  |                                                                                                                                    |
| Function / source references                                                                                           |                                                                                               |                                                  |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keyflow_gui.go (optKeep/optLogin/optCreate/optPaste/optSkip), keysetup_darwin.go |                                                                                               |                                                  |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keydialog_windows.go                                                             |                                                                                               |                                                  |                                                                                                                                    |
| platform/windows/scripts/user-token.ps1                                                                                |                                                                                               |                                                  |                                                                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/keyflow_gui.go (zenity), keysetup_linux.go                                       |                                                                                               |                                                  |                                                                                                                                    |
| API id                                                                                                                 | Method                                                                                        | Path                                             | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                                                                                    | GET                                                                                           | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                                                                                           | —                                                                                             | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                                                                                          | POST                                                                                          | sign.verae.ai/sign/v1/requests                   | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                                                                                           | POST                                                                                          | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| portal.login                                                                                                           | POST                                                                                          | customer.verae.ai/portal/api/login               | email:string, password:string, totpCode:string (6 digits)                                                                          |
| portal.2fa                                                                                                             | GET/POST/DELETE                                                                               | customer.verae.ai/portal/api/2fa/*               | setup:POST {}, code:string, totpCode:string                                                                                        |
| sign.public.sign                                                                                                       | POST                                                                                          | sign.verae.ai/sign/v1/public/:token/sign         | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

PT-W3 — Menu bar status + notifications (Mac)

Ambient job status after printing: menu bar extra with waiting/held jobs; notifications for 'certificate ready' and 'held'.



PT-06


PT-W3

| Features                                                                             |        |                                                                                     |                                                                                    |
|--------------------------------------------------------------------------------------|--------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Menu bar extra: waiting / held jobs with stage text.                               |        | • Notification when final (certificate ready) and when held (sign in).              |                                                                                    |
| • Tray flyout: printer health + recent jobs with state badges.                       |        | • Toast for held job with Sign in action (also 'Certificate ready' toast on final). |                                                                                    |
| Function / source references                                                         |        |                                                                                     |                                                                                    |
| New (PR3)                                                                            |        |                                                                                     |                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/serve.go, hide_windows.go, platform_windows.go |        |                                                                                     |                                                                                    |
| lib/files/file_browser.dart                                                          |        |                                                                                     |                                                                                    |
| lib/timestamps/auto_stamp.dart                                                       |        |                                                                                     |                                                                                    |
| API id                                                                               | Method | Path                                                                                | Key params (name:type)                                                             |
| peergos.cube                                                                         | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                                    | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                         | POST   | customer.verae.ai/v1/timestamp                                                      | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

PT-W4 — Print job queue + receipt status

New window listing every printed job with its receipt state — today success/pending are only visible as files appearing in a folder (U-w3).



PT-04

PT-W4

PT-L3


| Features                                                                                                                                                                                                                                                                                                        |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>• Held-job banner: 401/403 jobs are kept in the pending folder and retried after a new key (pending.go).</li><li>• Detail: state, multihash, timeline, output files; certificate only after final; never uses the local clock (PR1).</li><li>• Held-job banner.</li></ul> |        | <ul style="list-style-type: none"><li>• Job table: document, source app, multihash, receipt state. A pending zap response is held as 'Pending receipt' — never failed and never shown as a jobId (PR2).</li><li>• InfoBar for held jobs; same table/detail components; settings page mirrors PT-07 (route, output folder, Signed/).</li><li>• Notification on final / held with actions.</li></ul> |                                                                                    |
| Function / source references                                                                                                                                                                                                                                                                                    |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| PrintToVeraeTimeStamp/cmd/verae-print/pending.go, stampcore.go, serve.go                                                                                                                                                                                                                                        |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| internal/job/job.go                                                                                                                                                                                                                                                                                             |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| internal/veraeapi/client.go                                                                                                                                                                                                                                                                                     |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| PrintToVeraeTimeStamp/internal/job/job.go                                                                                                                                                                                                                                                                       |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| PrintToVeraeTimeStamp/platform/Linux/README.txt                                                                                                                                                                                                                                                                 |        |                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                    |
| API id                                                                                                                                                                                                                                                                                                          | Method | Path                                                                                                                                                                                                                                                                                                                                                                                               | Key params (name:type)                                                             |
| v1.timestamp.status                                                                                                                                                                                                                                                                                             | GET    | customer.verae.ai/v1/timestamp/status                                                                                                                                                                                                                                                                                                                                                              | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                                                                                                                                                                                                                                                    | —      | peergos.verae.ai (Peergos HTTP/API + local rust)                                                                                                                                                                                                                                                                                                                                                   | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                                                                                                                                                                                                                                                    | POST   | customer.verae.ai/v1/timestamp                                                                                                                                                                                                                                                                                                                                                                     | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → [VERAE-API-REFERENCE.pdf](#)



SG-I1 — iOS — signature request + sign

Push notification opens the native sign screen; Face ID confirms; the signature event is stamped.

| ios                                                                                                                                                     |        | android                                                                                                                                                                              |                                                                                                                                    |  |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|--|--|
|                                                                        |        |                                                                                                   |                                                                                                                                    |  |  |
| SG-I1                                                                                                                                                   |        | SG-A1                                                                                                                                                                                |                                                                                                                                    |  |  |
| Features                                                                                                                                                |        |                                                                                                                                                                                      |                                                                                                                                    |  |  |
| <ul style="list-style-type: none"><li>• Push notification (APNs).</li><li>• Signature field (PencilKit draw / type).</li><li>• Document card.</li></ul> |        | <ul style="list-style-type: none"><li>• Document card with original's final receipt.</li><li>• Consent + Face ID confirmation.</li><li>• Signature canvas (stylus/finger).</li></ul> |                                                                                                                                    |  |  |
| Function / source references                                                                                                                            |        |                                                                                                                                                                                      |                                                                                                                                    |  |  |
| verae-sign /sign/v1 on sign.verae.ai (edge)                                                                                                             |        |                                                                                                                                                                                      |                                                                                                                                    |  |  |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier                                                                                              |        |                                                                                                                                                                                      |                                                                                                                                    |  |  |
| digests only                                                                                                                                            |        |                                                                                                                                                                                      |                                                                                                                                    |  |  |
| peergos-flutter app shell                                                                                                                               |        |                                                                                                                                                                                      |                                                                                                                                    |  |  |
| lib/sign/sign_api.dart                                                                                                                                  |        |                                                                                                                                                                                      |                                                                                                                                    |  |  |
| lib/sign/sign_screens.dart                                                                                                                              |        |                                                                                                                                                                                      |                                                                                                                                    |  |  |
| API id                                                                                                                                                  | Method | Path                                                                                                                                                                                 | Key params (name:type)                                                                                                             |  |  |
| v1.timestamp.status                                                                                                                                     | GET    | customer.verae.ai/v1/timestamp/status                                                                                                                                                | sha256:string (64 hex), jobId:string?                                                                                              |  |  |
| sign.requests                                                                                                                                           | POST   | sign.verae.ai/sign/v1/requests                                                                                                                                                       | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |  |  |
| sign.public.sign                                                                                                                                        | POST   | sign.verae.ai/sign/v1/public/:token/sign                                                                                                                                             | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |  |  |
| v1.timestamp                                                                                                                                            | POST   | customer.verae.ai/v1/timestamp                                                                                                                                                       | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |  |  |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

SG-I2 — iOS — send for signature (from a cube file)


Start a request from a file in a DataCube (share menu → Send for signature).



SG-I2

SG-M1

SG-WN1




SG-W1

| Features                                                   |              |                                                                            |                                                                                                                                    |
|------------------------------------------------------------|--------------|----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Signer list from contacts.                               |              | • What-gets-stamped note.                                                  |                                                                                                                                    |
| • Signers.                                                 |              | • Stamping explanation; notifications per step.                            |                                                                                                                                    |
| • Signer entry from print dialog.                          |              | • Already-registered original reuses receipt.                              |                                                                                                                                    |
| • Document with placed signature fields and its multihash. |              | • Ordered signers.                                                         |                                                                                                                                    |
| • Email OTP + ordering options.                            |              | • Plain explanation of what is stamped (send, each signature, completion). |                                                                                                                                    |
| Function / source references                               |              |                                                                            |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |              |                                                                            |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |              |                                                                            |                                                                                                                                    |
| digests only                                               |              |                                                                            |                                                                                                                                    |
| printit Windows print server                               |              |                                                                            |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |              |                                                                            |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |              |                                                                            |                                                                                                                                    |
| API id                                                     | Method       | Path                                                                       | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET          | customer.verae.ai/v1/timestamp/status                                      | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                               | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                           | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                              | POST         | sign.verae.ai/sign/v1/requests                                             | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                               | POST         | customer.verae.ai/v1/timestamp                                             | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| add.destination                                            | local + APIs | App add flow (DC-07D)                                                      | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ...                |
| sign.public.sign                                           | POST         | sign.verae.ai/sign/v1/public/:token/sign                                   | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

SG-L1 — Debian GNOME — completion notification + Signed folder

Linux helper shows a GNOME notification on completion and drops files into ~/Verae/Signed.



SG-L1

SG-W5

| Features                                                   |        |                                                  |                                                                                                                                    |
|------------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Signed folder listing with receipt states.               |        | • Notification (libnotify) with action.          |                                                                                                                                    |
| • Delivery fan-out per party + DataCube save.              |        | • Files with final receipts.                     |                                                                                                                                    |
| • Verify QR/link.                                          |        |                                                  |                                                                                                                                    |
| Function / source references                               |        |                                                  |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |        |                                                  |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |        |                                                  |                                                                                                                                    |
| digests only                                               |        |                                                  |                                                                                                                                    |
| printit Linux CUPS helper                                  |        |                                                  |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |        |                                                  |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |        |                                                  |                                                                                                                                    |
| API id                                                     | Method | Path                                             | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                               | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                              | POST   | sign.verae.ai/sign/v1/requests                   | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                               | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| sign.public.sign                                           | POST   | sign.verae.ai/sign/v1/public/:token/sign         | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERA-API-REFERENCE.pdf

SG-M1 — iOS — send for signature (from a cube file)


Start a request from a file in a DataCube (share menu → Send for signature).



SG-I2

SG-M1

SG-WN1




SG-W1

| Features                                                   |              |                                                                            |                                                                                                                                    |
|------------------------------------------------------------|--------------|----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Signer list from contacts.                               |              | • What-gets-stamped note.                                                  |                                                                                                                                    |
| • Signers.                                                 |              | • Stamping explanation; notifications per step.                            |                                                                                                                                    |
| • Signer entry from print dialog.                          |              | • Already-registered original reuses receipt.                              |                                                                                                                                    |
| • Document with placed signature fields and its multihash. |              | • Ordered signers.                                                         |                                                                                                                                    |
| • Email OTP + ordering options.                            |              | • Plain explanation of what is stamped (send, each signature, completion). |                                                                                                                                    |
| Function / source references                               |              |                                                                            |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |              |                                                                            |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |              |                                                                            |                                                                                                                                    |
| digests only                                               |              |                                                                            |                                                                                                                                    |
| printit Windows print server                               |              |                                                                            |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |              |                                                                            |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |              |                                                                            |                                                                                                                                    |
| API id                                                     | Method       | Path                                                                       | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET          | customer.verae.ai/v1/timestamp/status                                      | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                               | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                           | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                              | POST         | sign.verae.ai/sign/v1/requests                                             | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                               | POST         | customer.verae.ai/v1/timestamp                                             | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| add.destination                                            | local + APIs | App add flow (DC-07D)                                                      | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ...                |
| sign.public.sign                                           | POST         | sign.verae.ai/sign/v1/public/:token/sign                                   | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

SG-P1 — Signature audit certificate (PDF)

Certificate delivered with the signed PDF: hashes, every step with its Substrate block, verify QR.



SG-P1

| Features                                                   |        |                                                  |                                                                                                                                    |
|------------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Original + signed hashes and overall state.              |        | • Per-step table with block numbers.             |                                                                                                                                    |
| • Verify QR + instructions.                                |        |                                                  |                                                                                                                                    |
| Function / source references                               |        |                                                  |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |        |                                                  |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |        |                                                  |                                                                                                                                    |
| digests only                                               |        |                                                  |                                                                                                                                    |
| printit/pdfcert.go layout                                  |        |                                                  |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |        |                                                  |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |        |                                                  |                                                                                                                                    |
| API id                                                     | Method | Path                                             | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                               | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                              | POST   | sign.verae.ai/sign/v1/requests                   | documentSha256:string 64 hex, documentName:string, signers:array<(email:string,name?:string)>, title:string?, message:string?, ... |
| v1.timestamp                                               | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| sign.public.sign                                           | POST   | sign.verae.ai/sign/v1/public/:token/sign         | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

SG-W1 — iOS — send for signature (from a cube file)


Start a request from a file in a DataCube (share menu → Send for signature).



SG-I2

SG-M1

SG-WN1




SG-W1

| Features                                                   |              |                                                                            |                                                                                                                                    |
|------------------------------------------------------------|--------------|----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Signer list from contacts.                               |              | • What-gets-stamped note.                                                  |                                                                                                                                    |
| • Signers.                                                 |              | • Stamping explanation; notifications per step.                            |                                                                                                                                    |
| • Signer entry from print dialog.                          |              | • Already-registered original reuses receipt.                              |                                                                                                                                    |
| • Document with placed signature fields and its multihash. |              | • Ordered signers.                                                         |                                                                                                                                    |
| • Email OTP + ordering options.                            |              | • Plain explanation of what is stamped (send, each signature, completion). |                                                                                                                                    |
| Function / source references                               |              |                                                                            |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |              |                                                                            |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |              |                                                                            |                                                                                                                                    |
| digests only                                               |              |                                                                            |                                                                                                                                    |
| printit Windows print server                               |              |                                                                            |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |              |                                                                            |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |              |                                                                            |                                                                                                                                    |
| API id                                                     | Method       | Path                                                                       | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET          | customer.verae.ai/v1/timestamp/status                                      | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                               | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                           | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                              | POST         | sign.verae.ai/sign/v1/requests                                             | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                               | POST         | customer.verae.ai/v1/timestamp                                             | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| add.destination                                            | local + APIs | App add flow (DC-07D)                                                      | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ...                |
| sign.public.sign                                           | POST         | sign.verae.ai/sign/v1/public/:token/sign                                   | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERA-API-REFERENCE.pdf

## SG-W2 — Request status — step stamps

Live progress with one receipt per step; never a job id.




SG-W2

| Features                                                   |        |                                          |                                                                                                                                    |
|------------------------------------------------------------|--------|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Step list with Substrate state per step.                 |        | • Signer status.                         |                                                                                                                                    |
| • Pending finality explanation; void is stamped.           |        |                                          |                                                                                                                                    |
| Function / source references                               |        |                                          |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |        |                                          |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |        |                                          |                                                                                                                                    |
| digests only                                               |        |                                          |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |        |                                          |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |        |                                          |                                                                                                                                    |
| API id                                                     | Method | Path                                     | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET    | customer.verae.ai/v1/timestamp/status    | sha256:string (64 hex), jobId:string?                                                                                              |
| sign.requests                                              | POST   | sign.verae.ai/sign/v1/requests           | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| sign.public.sign                                           | POST   | sign.verae.ai/sign/v1/public/:token/sign | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |
| v1.timestamp                                               | POST   | customer.verae.ai/v1/timestamp           | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

### SG-W3 — Signer landing + email OTP

Account-free signer entry from the email link; identity proven by a one-time code.




SG-W3

| Features                                                   |        |                                          |                                                                                                                                    |
|------------------------------------------------------------|--------|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • OTP to the invited address.                              |        | • Privacy/audit note.                    |                                                                                                                                    |
| Function / source references                               |        |                                          |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |        |                                          |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |        |                                          |                                                                                                                                    |
| digests only                                               |        |                                          |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |        |                                          |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |        |                                          |                                                                                                                                    |
| API id                                                     | Method | Path                                     | Key params (name:type)                                                                                                             |
| sign.requests                                              | POST   | sign.verae.ai/sign/v1/requests           | documentSha256:string 64 hex, documentName:string, signers:array<(email:string,name?:string)>, title:string?, message:string?, ... |
| sign.public.sign                                           | POST   | sign.verae.ai/sign/v1/public/:token/sign | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |
| v1.timestamp                                               | POST   | customer.verae.ai/v1/timestamp           | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

SG-W4 — Sign — draw / type / upload + consent

Signature capture with explicit e-sign consent; submitting stamps the signature event.




SG-W4

| Features                                                   |              |                                                  |                                                                                                                                    |
|------------------------------------------------------------|--------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Draw/Type/Upload signature.                              |              | • Consent text that names the blockchain record. |                                                                                                                                    |
| • Decline (stamped with reason) or Sign.                   |              |                                                  |                                                                                                                                    |
| Function / source references                               |              |                                                  |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |              |                                                  |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |              |                                                  |                                                                                                                                    |
| digests only                                               |              |                                                  |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |              |                                                  |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |              |                                                  |                                                                                                                                    |
| API id                                                     | Method       | Path                                             | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET          | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                                              |
| peergos.cube                                               | —            | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                              | POST         | sign.verae.ai/sign/v1/requests                   | documentSha256:string 64 hex, documentName:string, signers:array<(email:string,name?:string)>, title:string?, message:string?, ... |
| v1.timestamp                                               | POST         | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |
| add.destination                                            | local + APIs | App add flow (DC-07D)                            | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ...                |
| sign.public.sign                                           | POST         | sign.verae.ai/sign/v1/public/:token/sign         | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

SG-W5 — Debian GNOME — completion notification + Signed folder

Linux helper shows a GNOME notification on completion and drops files into ~/Veræ/Signed.



SG-L1

SG-W5

| Features                                                   |        |                                                  |                                                                                                                                    |
|------------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Signed folder listing with receipt states.               |        | • Notification (libnotify) with action.          |                                                                                                                                    |
| • Delivery fan-out per party + DataCube save.              |        | • Files with final receipts.                     |                                                                                                                                    |
| • Verify QR/link.                                          |        |                                                  |                                                                                                                                    |
| Function / source references                               |        |                                                  |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |        |                                                  |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |        |                                                  |                                                                                                                                    |
| digests only                                               |        |                                                  |                                                                                                                                    |
| printit Linux CUPS helper                                  |        |                                                  |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |        |                                                  |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |        |                                                  |                                                                                                                                    |
| API id                                                     | Method | Path                                             | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                                              |
| peergos.cube                                               | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                              | POST   | sign.verae.ai/sign/v1/requests                   | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                               | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                                 |
| sign.public.sign                                           | POST   | sign.verae.ai/sign/v1/public/:token/sign         | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERÆ-API-REFERENCE.pdf

SG-WN1 — iOS — send for signature (from a cube file)


Start a request from a file in a DataCube (share menu → Send for signature).



SG-I2

SG-M1

SG-WN1




SG-W1

| Features                                                   |              |                                                                            |                                                                                                                                    |
|------------------------------------------------------------|--------------|----------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| • Signer list from contacts.                               |              | • What-gets-stamped note.                                                  |                                                                                                                                    |
| • Signers.                                                 |              | • Stamping explanation; notifications per step.                            |                                                                                                                                    |
| • Signer entry from print dialog.                          |              | • Already-registered original reuses receipt.                              |                                                                                                                                    |
| • Document with placed signature fields and its multihash. |              | • Ordered signers.                                                         |                                                                                                                                    |
| • Email OTP + ordering options.                            |              | • Plain explanation of what is stamped (send, each signature, completion). |                                                                                                                                    |
| Function / source references                               |              |                                                                            |                                                                                                                                    |
| verae-sign /sign/v1 on sign.verae.ai (edge)                |              |                                                                            |                                                                                                                                    |
| stamps via /v1/timestamp on customer.verae.ai – not Zapier |              |                                                                            |                                                                                                                                    |
| digests only                                               |              |                                                                            |                                                                                                                                    |
| printit Windows print server                               |              |                                                                            |                                                                                                                                    |
| lib/sign/sign_api.dart                                     |              |                                                                            |                                                                                                                                    |
| lib/sign/sign_screens.dart                                 |              |                                                                            |                                                                                                                                    |
| API id                                                     | Method       | Path                                                                       | Key params (name:type)                                                                                                             |
| v1.timestamp.status                                        | GET          | customer.verae.ai/v1/timestamp/status                                      | sha256:string (64 hex), jobld:string?                                                                                              |
| peergos.cube                                               | —            | peergos.verae.ai (Peergos HTTP/API + local rust)                           | username:string, password:string, path:string, bytes:bytes                                                                         |
| sign.requests                                              | POST         | sign.verae.ai/sign/v1/requests                                             | documentSha256:string 64 hex, documentName:string, signers:array<{email:string,name?:string}>, title:string?, message:string?, ... |
| v1.timestamp                                               | POST         | customer.verae.ai/v1/timestamp                                             | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                                 |
| add.destination                                            | local + APIs | App add flow (DC-07D)                                                      | uploadPeergos:boolean, addTags:boolean, timestampRegistry:boolean, tags:string[], metadataJsonl:string (JSONL), ...                |
| sign.public.sign                                           | POST         | sign.verae.ai/sign/v1/public/:token/sign                                   | token:path string, email:string, otp:string, signatureSha256:string 64 hex, kind:'draw' 'type' 'upload', ...                       |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-01 — Portal sign-in + 2FA

Customer sign-in (email + password, optional TOTP), sign-up or claim an account created by sales; staff are routed to IAM (portal/index.html #auth-form).




ZP-01

| Features                                                                     |                 |                                                                                                |                                                                                                                               |
|------------------------------------------------------------------------------|-----------------|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Rebranded from 'Zappier Portal' to Verae.                                  |                 | • Email/password; links to reset, sign-up and claim; staff → iam.verae.ai. Variant: TOTP step. |                                                                                                                               |
| Function / source references                                                 |                 |                                                                                                |                                                                                                                               |
| veb/ (verae-edge-billing) portal/index.html (#auth), docs/CUSTOMER-PORTAL.md |                 |                                                                                                |                                                                                                                               |
| API id                                                                       | Method          | Path                                                                                           | Key params (name:type)                                                                                                        |
| portal.profile                                                               | GET/PATCH       | customer.verae.ai/portal/api/profile                                                           | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| portal.usage                                                                 | GET             | customer.verae.ai/portal/api/usage                                                             | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                                                | GET/POST/DELETE | customer.verae.ai/portal/api/tokens                                                            | name:string, id:string                                                                                                        |
| portal.login                                                                 | POST            | customer.verae.ai/portal/api/login                                                             | email:string, password:string, totpCode:string (6 digits)                                                                     |
| portal.billing                                                               | GET/POST        | customer.verae.ai/portal/api/billing/*                                                         | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.2fa                                                                   | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*                                                             | setup:POST {}, code:string, totpCode:string                                                                                   |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

ZP-02 — Portal — mobile responsive

Dashboard reflowed for phones: stacked KPIs, bottom tab bar.



ZP-09

| Features                                                    |                 |                                                  |                                                                                                                               |
|-------------------------------------------------------------|-----------------|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Stacked KPIs (single column under 600 px).                |                 | • Receipt health chips.                          |                                                                                                                               |
| Function / source references                                |                 |                                                  |                                                                                                                               |
| veb/ (verae-edge-billing) portal/index.html (viewport meta) |                 |                                                  |                                                                                                                               |
| API id                                                      | Method          | Path                                             | Key params (name:type)                                                                                                        |
| v1.timestamp.status                                         | GET             | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                                         |
| peergos.cube                                                | —               | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                    |
| portal.usage                                                | GET             | customer.verae.ai/portal/api/usage               | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                               | GET/POST/DELETE | customer.verae.ai/portal/api/tokens              | name:string, id:string                                                                                                        |
| portal.billing                                              | GET/POST        | customer.verae.ai/portal/api/billing/*           | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                              | GET/PATCH       | customer.verae.ai/portal/api/profile             | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

ZP-03 — Usage & metering detail

Per-endpoint metered usage with the pricing rule, customer-type multiplier and monthly credit (USER-MANUAL §3).

web


ZP-03

| Features                                         |                 |                                                                     |                                                                                                                               |
|--------------------------------------------------|-----------------|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Period/key/endpoint filters + CSV export.      |                 | • Rule → list → multiplier → total; existing-hash lookups are free. |                                                                                                                               |
| • Quote-per-call explanation.                    |                 |                                                                     |                                                                                                                               |
| Function / source references                     |                 |                                                                     |                                                                                                                               |
| veb/ (verae-edge-billing) docs/USER-MANUAL.md §3 |                 |                                                                     |                                                                                                                               |
| src/pricing                                      |                 |                                                                     |                                                                                                                               |
| API id                                           | Method          | Path                                                                | Key params (name:type)                                                                                                        |
| portal.billing                                   | GET/POST        | customer.verae.ai/portal/api/billing/*                              | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                   | GET/PATCH       | customer.verae.ai/portal/api/profile                                | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| portal.usage                                     | GET             | customer.verae.ai/portal/api/usage                                  | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                    | GET/POST/DELETE | customer.verae.ai/portal/api/tokens                                 | name:string, id:string                                                                                                        |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-04 — Invoices

Invoice history with status, PO number, print view and email-invoicing preferences (portal Invoices tab).




ZP-04

| Features                                           |                 |                                        |                                                                                                                               |
|----------------------------------------------------|-----------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Invoice table (draft hidden from customers).     |                 | • Email invoicing preference.          |                                                                                                                               |
| • Invoice PDF stamped (proposal).                  |                 |                                        |                                                                                                                               |
| Function / source references                       |                 |                                        |                                                                                                                               |
| veb/ (verae-edge-billing) portal data-tab=invoices |                 |                                        |                                                                                                                               |
| docs/ACCOUNTING.md                                 |                 |                                        |                                                                                                                               |
| API id                                             | Method          | Path                                   | Key params (name:type)                                                                                                        |
| v1.timestamp                                       | POST            | customer.verae.ai/v1/timestamp         | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                            |
| portal.usage                                       | GET             | customer.verae.ai/portal/api/usage     | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                      | GET/POST/DELETE | customer.verae.ai/portal/api/tokens    | name:string, id:string                                                                                                        |
| portal.billing                                     | GET/POST        | customer.verae.ai/portal/api/billing/* | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                     | GET/PATCH       | customer.verae.ai/portal/api/profile   | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

### ZP-05 — Statement (ledger)

Chronological ledger of debits/credits and running balance (portal Statement tab).




**ZP-05**

| Features                                            |                 |                                                  |                                                                                                                               |
|-----------------------------------------------------|-----------------|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Ledger with running balance.                      |                 | • Exports.                                       |                                                                                                                               |
| Function / source references                        |                 |                                                  |                                                                                                                               |
| veb/ (verae-edge-billing) portal data-tab=statement |                 |                                                  |                                                                                                                               |
| API id                                              | Method          | Path                                             | Key params (name:type)                                                                                                        |
| peergos.cube                                        | —               | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                    |
| portal.usage                                        | GET             | customer.verae.ai/portal/api/usage               | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                       | GET/POST/DELETE | customer.verae.ai/portal/api/tokens              | name:string, id:string                                                                                                        |
| portal.billing                                      | GET/POST        | customer.verae.ai/portal/api/billing/*           | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                      | GET/PATCH       | customer.verae.ai/portal/api/profile             | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |

Sample calls + full param tables → [VERAE-API-REFERENCE.pdf](#)

ZP-06 — Billing — balance, reload, cards, PO

Prepaid balance reloads, auto-reload, Stripe cards and PO billing request (portal Billing tab; flutter usage\_billing Cards/PO tabs).




ZP-06

| Features                                              |                 |                                                  |                                                                                                                               |
|-------------------------------------------------------|-----------------|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Balance + reload presets.                           |                 | • Auto-reload threshold.                         |                                                                                                                               |
| • Cards (Stripe Elements).                            |                 | • PO billing request.                            |                                                                                                                               |
| Function / source references                          |                 |                                                  |                                                                                                                               |
| veb/ (verae-edge-billing) portal data-tab=billing     |                 |                                                  |                                                                                                                               |
| peergos-flutter lib/billing/usage_billing_screen.dart |                 |                                                  |                                                                                                                               |
| lib/files/file_browser.dart                           |                 |                                                  |                                                                                                                               |
| lib/timestamps/auto_stamp.dart                        |                 |                                                  |                                                                                                                               |
| API id                                                | Method          | Path                                             | Key params (name:type)                                                                                                        |
| peergos.cube                                          | —               | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                    |
| portal.usage                                          | GET             | customer.verae.ai/portal/api/usage               | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                         | GET/POST/DELETE | customer.verae.ai/portal/api/tokens              | name:string, id:string                                                                                                        |
| portal.billing                                        | GET/POST        | customer.verae.ai/portal/api/billing/*           | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                        | GET/PATCH       | customer.verae.ai/portal/api/profile             | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

ZP-07 — Security — API keys (xVerae-) & 2FA

Create/revoke named, scoped API keys (shown once) and manage TOTP 2FA (portal Security tab).



ZP-07


| Features                                                                                                                                       |                                                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• Key list (masked) with scope, last used, revoke.</li> <li>• 2FA status and recovery codes.</li> </ul> | <ul style="list-style-type: none"> <li>• One-time reveal of a new xVerae- key with copy.</li> </ul> |

| Function / source references                                                                                                                  |                 |                                        |                                                                                                                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| veb/ (verae-edge-billing) portal data-tab=security<br>printit keyflow_gui.go<br>lib/files/file_browser.dart<br>lib/timestamps/auto_stamp.dart |                 |                                        |                                                                                                                               |
| API id                                                                                                                                        | Method          | Path                                   | Key params (name:type)                                                                                                        |
| v1.timestamp.status                                                                                                                           | GET             | customer.verae.ai/v1/timestamp/status  | sha256:string (64 hex), jobId:string?                                                                                         |
| v1.timestamp                                                                                                                                  | POST            | customer.verae.ai/v1/timestamp         | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object?                                            |
| portal.profile                                                                                                                                | GET/PATCH       | customer.verae.ai/portal/api/profile   | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| portal.usage                                                                                                                                  | GET             | customer.verae.ai/portal/api/usage     | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                                                                                                                 | GET/POST/DELETE | customer.verae.ai/portal/api/tokens    | name:string, id:string                                                                                                        |
| portal.login                                                                                                                                  | POST            | customer.verae.ai/portal/api/login     | email:string, password:string, totpCode:string (6 digits)                                                                     |
| portal.billing                                                                                                                                | GET/POST        | customer.verae.ai/portal/api/billing/* | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.2fa                                                                                                                                    | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/*     | setup:POST {}, code:string, totpCode:string                                                                                   |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-08 — API & pricing

Live per-plan pricing and API quick start; the example teaches the receipt lifecycle by hash, not jobld.




ZP-08

| Features                                       |                 |                                                   |                                                                                                                               |
|------------------------------------------------|-----------------|---------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Rate card at the customer's multiplier.      |                 | • Quick-start code with pending → final response. |                                                                                                                               |
| • No-jobld rule.                               |                 |                                                   |                                                                                                                               |
| Function / source references                   |                 |                                                   |                                                                                                                               |
| veb/ (verae-edge-billing) portal data-tab=docs |                 |                                                   |                                                                                                                               |
| openapi.yaml                                   |                 |                                                   |                                                                                                                               |
| API id                                         | Method          | Path                                              | Key params (name:type)                                                                                                        |
| v1.timestamp.status                            | GET             | customer.verae.ai/v1/timestamp/status             | sha256:string (64 hex), jobld:string?                                                                                         |
| v1.timestamp                                   | POST            | customer.verae.ai/v1/timestamp                    | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object?                                            |
| portal.usage                                   | GET             | customer.verae.ai/portal/api/usage                | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                  | GET/POST/DELETE | customer.verae.ai/portal/api/tokens               | name:string, id:string                                                                                                        |
| portal.billing                                 | GET/POST        | customer.verae.ai/portal/api/billing/*            | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                 | GET/PATCH       | customer.verae.ai/portal/api/profile              | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-09 — Portal — mobile responsive

Dashboard reflowed for phones: stacked KPIs, bottom tab bar.




ZP-09

| Features                                                    |                 |                                                  |                                                                                                                               |
|-------------------------------------------------------------|-----------------|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Stacked KPIs (single column under 600 px).                |                 | • Receipt health chips.                          |                                                                                                                               |
| Function / source references                                |                 |                                                  |                                                                                                                               |
| veb/ (verae-edge-billing) portal/index.html (viewport meta) |                 |                                                  |                                                                                                                               |
| API id                                                      | Method          | Path                                             | Key params (name:type)                                                                                                        |
| v1.timestamp.status                                         | GET             | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                                                                         |
| peergos.cube                                                | —               | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                                                                    |
| portal.usage                                                | GET             | customer.verae.ai/portal/api/usage               | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                               | GET/POST/DELETE | customer.verae.ai/portal/api/tokens              | name:string, id:string                                                                                                        |
| portal.billing                                              | GET/POST        | customer.verae.ai/portal/api/billing/*           | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                              | GET/PATCH       | customer.verae.ai/portal/api/profile             | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-B0 — Staff sign-in (Verae IAM)

Single staff sign-in for admin, billing, CS, sales, finance and compliance (verae-staff-iam).




ZP-B0

| Features                                                    |                 |                                        |                                                                                                                               |
|-------------------------------------------------------------|-----------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • IAM-branded staff login (separate from customer portal).  |                 | • Mandatory TOTP.                      |                                                                                                                               |
| • mTLS device cert + forced password change on first login. |                 |                                        |                                                                                                                               |
| Function / source references                                |                 |                                        |                                                                                                                               |
| verae-staff-iam/public, docs (forcepw, mtls bundles)        |                 |                                        |                                                                                                                               |
| API id                                                      | Method          | Path                                   | Key params (name:type)                                                                                                        |
| portal.billing                                              | GET/POST        | customer.verae.ai/portal/api/billing/* | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                              | GET/PATCH       | customer.verae.ai/portal/api/profile   | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| portal.usage                                                | GET             | customer.verae.ai/portal/api/usage     | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                               | GET/POST/DELETE | customer.verae.ai/portal/api/tokens    | name:string, id:string                                                                                                        |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-B1 — Admin — customers

Customer list with type, billing method, MTD, balance; create customer (key shown once) (admin Customers tab).




ZP-B1

| Features                                                      |                 |                                        |                                                                                                                               |
|---------------------------------------------------------------|-----------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Customer table with status (balance empty, unclaimed).      |                 | • Create with type/billing/override.   |                                                                                                                               |
| Function / source references                                  |                 |                                        |                                                                                                                               |
| veb/ (verae-edge-billing) admin/index.html data-tab=customers |                 |                                        |                                                                                                                               |
| USER-MANUAL §4.3                                              |                 |                                        |                                                                                                                               |
| API id                                                        | Method          | Path                                   | Key params (name:type)                                                                                                        |
| portal.billing                                                | GET/POST        | customer.verae.ai/portal/api/billing/* | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                                | GET/PATCH       | customer.verae.ai/portal/api/profile   | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| portal.usage                                                  | GET             | customer.verae.ai/portal/api/usage     | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                                 | GET/POST/DELETE | customer.verae.ai/portal/api/tokens    | name:string, id:string                                                                                                        |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## ZP-B2 — Customer support lookup

CS resolves receipt questions by hash/key/customer; diagnoses client vs chain; read-only impersonation, audit-logged.




ZP-B2

| Features                                           |        |                                                          |                                                                                    |
|----------------------------------------------------|--------|----------------------------------------------------------|------------------------------------------------------------------------------------|
| • Hash lookup showing chain truth vs client state. |        | • Diagnosis + safe actions (email receipt, verify link). |                                                                                    |
| • Account summary; read-only impersonation.        |        |                                                          |                                                                                    |
| Function / source references                       |        |                                                          |                                                                                    |
| proposal                                           |        |                                                          |                                                                                    |
| web admin Customers                                |        |                                                          |                                                                                    |
| verae-staff-iam roles                              |        |                                                          |                                                                                    |
| API id                                             | Method | Path                                                     | Key params (name:type)                                                             |
| v1.timestamp.status                                | GET    | customer.verae.ai/v1/timestamp/status                    | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                       | —      | peergos.verae.ai (Peergos HTTP/API + local rust)         | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                       | POST   | customer.verae.ai/v1/timestamp                           | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

ZP-B3 — Sales — pipeline & quotes

Pipeline and quote builder using rate-card types/overrides; quotes sent stamped or via signing round-trip.




ZP-B3

| Features                       |        |                                                                  |                                                                                    |
|--------------------------------|--------|------------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Kanban pipeline.             |        | • Quote builder → stamped PDF or SG signing; approval guardrail. |                                                                                    |
| Function / source references   |        |                                                                  |                                                                                    |
| proposal                       |        |                                                                  |                                                                                    |
| web Customer types / overrides |        |                                                                  |                                                                                    |
| API id                         | Method | Path                                                             | Key params (name:type)                                                             |
| v1.timestamp.status            | GET    | customer.verae.ai/v1/timestamp/status                            | sha256:string (64 hex), jobId:string?                                              |
| v1.timestamp                   | POST   | customer.verae.ai/v1/timestamp                                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-B4 — Admin — rate card & customer types

Per-endpoint pricing (free/fixed/variable) and tier multipliers/credits; increases gated by approval (admin Rate card + Customer types tabs).




ZP-B4

| Features                                                                           |        |                                                  |                                                            |
|------------------------------------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------|
| • Editable rate card (operationId must match openapi.yaml; delete = endpoint off). |        | • Types: multiplier + monthly credit.            |                                                            |
| • Impact preview + 2-person approval (proposal).                                   |        |                                                  |                                                            |
| Function / source references                                                       |        |                                                  |                                                            |
| veb/ (verae-edge-billing) admin data-tab=endpoints, tiers                          |        |                                                  |                                                            |
| USER-MANUAL §4.1–4.2                                                               |        |                                                  |                                                            |
| API id                                                                             | Method | Path                                             | Key params (name:type)                                     |
| peergos.cube                                                                       | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-B5 — Finance — invoices, reconciliation, period close

Month-end checklist: lock usage, reconcile Stripe meter vs ledger, issue invoices (draft→issued→paid), export journal, close period.



ZP-B5

| Features                                                     |                 |                                                     |                                                                                                                               |
|--------------------------------------------------------------|-----------------|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Close checklist.                                           |                 | • Billed/collected/outstanding/reconciliation KPIs. |                                                                                                                               |
| • Invoice states with actions.                               |                 | • Export + close (ledger digest stamped).           |                                                                                                                               |
| Function / source references                                 |                 |                                                     |                                                                                                                               |
| veb/ (verae-edge-billing) admin data-tab=invoices, statement |                 |                                                     |                                                                                                                               |
| docs/ACCOUNTING.md                                           |                 |                                                     |                                                                                                                               |
| USER-MANUAL §6                                               |                 |                                                     |                                                                                                                               |
| API id                                                       | Method          | Path                                                | Key params (name:type)                                                                                                        |
| portal.billing                                               | GET/POST        | customer.verae.ai/portal/api/billing/*              | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                               | GET/PATCH       | customer.verae.ai/portal/api/profile                | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| portal.usage                                                 | GET             | customer.verae.ai/portal/api/usage                  | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                                | GET/POST/DELETE | customer.verae.ai/portal/api/tokens                 | name:string, id:string                                                                                                        |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

ZP-B6 — Finance — reports

Date-ranged billing reports by customer/type with CSV and usage-trend charts (admin Reports tab).

web

The screenshot shows the 'Reports' section of the Verae admin interface. It features a line chart titled 'Usage trend (seconds)' comparing 'Stamps' (solid line) and 'Revenue' (dashed line) over time. Below the chart is a table with columns: TYPE, CUSTOMERS, STAMPS, REVENUE, and CREDIT CARD. The table lists data for 'Enterprise', 'Pro', 'Startup', and 'Free' customer types.

| TYPE       | CUSTOMERS | STAMPS | REVENUE   | CREDIT CARD |
|------------|-----------|--------|-----------|-------------|
| Enterprise | 25        | 5,500  | \$176,250 | \$1,800     |
| Pro        | 475       | 3,400  | \$83,475  | \$6,750     |
| Startup    | 400       | 765    | \$13,875  | \$0         |
| Free       | 225       | 276    | \$0       | \$225       |


ZP-B6

| Features                                         |                 |                                        |                                                                                                                               |
|--------------------------------------------------|-----------------|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| • Filters + CSV.                                 |                 |                                        | • Trend chart (stamps vs revenue).                                                                                            |
| • Breakdown by type.                             |                 |                                        |                                                                                                                               |
| Function / source references                     |                 |                                        |                                                                                                                               |
| veb/ (verae-edge-billing) admin data-tab=reports |                 |                                        |                                                                                                                               |
| API id                                           | Method          | Path                                   | Key params (name:type)                                                                                                        |
| portal.billing                                   | GET/POST        | customer.verae.ai/portal/api/billing/* | methods:GET, reload:POST {amountCents:number}, po-request:POST {poNumber,terms}                                               |
| portal.profile                                   | GET/PATCH       | customer.verae.ai/portal/api/profile   | Authorization:header string, name,companyName,groupName,...:string, billingType:'stripe' 'purchase_order', phone:string E.164 |
| portal.usage                                     | GET             | customer.verae.ai/portal/api/usage     | peergosUsername:string?, from,to:ISO date?                                                                                    |
| portal.tokens                                    | GET/POST/DELETE | customer.verae.ai/portal/api/tokens    | name:string, id:string                                                                                                        |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-B7 — Compliance — audit log, evidence packs, chain hardening

Staff audit log (itself stamped), evidence-pack export, and the chain-hardening checklist that gates production claims.




ZP-B7

| Features                                          |        |                                                  |                                                                                    |
|---------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Hardening checklist gating certificate wording. |        | • Evidence pack builder.                         |                                                                                    |
| • Staff audit log with receipt states.            |        |                                                  |                                                                                    |
| Function / source references                      |        |                                                  |                                                                                    |
| verae-staff-iam Audit tab                         |        |                                                  |                                                                                    |
| itad docs 16 §11                                  |        |                                                  |                                                                                    |
| proposal                                          |        |                                                  |                                                                                    |
| API id                                            | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status                               | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                      | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                      | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-B8 — Admin — system health & users

Integration health (registrar, finality, Stripe job, Zapier, NATS) and admin users (admin System + Users tabs).




| ZP-B8                                                  |        |                                                  |                                                            |
|--------------------------------------------------------|--------|--------------------------------------------------|------------------------------------------------------------|
| Features                                               |        |                                                  |                                                            |
| • Health KPIs.                                         |        |                                                  |                                                            |
| • Admin users → IAM.                                   |        |                                                  |                                                            |
|                                                        |        | • Integration table.                             |                                                            |
| Function / source references                           |        |                                                  |                                                            |
| veb/ (verae-edge-billing) admin data-tab=system, users |        |                                                  |                                                            |
| NATS.md                                                |        |                                                  |                                                            |
| API id                                                 | Method | Path                                             | Key params (name:type)                                     |
| peergos.cube                                           | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-B9 — Staff IAM — people, roles & interface switcher

Grant per-person interfaces (Admin/Finance/Support/Sales/Compliance), see 2FA/device-cert status; drives the interface switcher (verae-staff-iam).




ZP-B9

| Features                                                          |                 |                                    |                                                                                    |
|-------------------------------------------------------------------|-----------------|------------------------------------|------------------------------------------------------------------------------------|
| • People table with security posture.                             |                 | • Per-interface toggles.           |                                                                                    |
| • Switcher preview.                                               |                 |                                    |                                                                                    |
| Function / source references                                      |                 |                                    |                                                                                    |
| verae-staff-iam/public (People & roles, Catalog, Audit, Security) |                 |                                    |                                                                                    |
| API id                                                            | Method          | Path                               | Key params (name:type)                                                             |
| portal.login                                                      | POST            | customer.verae.ai/portal/api/login | email:string, password:string, totpCode:string (6 digits)                          |
| portal.2fa                                                        | GET/POST/DELETE | customer.verae.ai/portal/api/2fa/* | setup:POST {}, code:string, totpCode:string                                        |
| v1.timestamp                                                      | POST            | customer.verae.ai/v1/timestamp     | sha256:string (64 hex), restamp:boolean, restampOf:string jobld?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

## ZP-V1 — Verify — entry (file, hash, QR)

Public, account-free verification: drop a file (hashed locally), paste a multihash/hex, scan a certificate QR or open a receipt file.




ZP-V1

| Features                                                     |        |                                                   |                                                                                    |
|--------------------------------------------------------------|--------|---------------------------------------------------|------------------------------------------------------------------------------------|
| • Local hashing drop zone (Web Crypto; file never uploaded). |        | • Hash input: multihash or bare 64-hex = SHA-256. |                                                                                    |
| • QR scan / receipt-file entry.                              |        | • Plain-language evidence rule.                   |                                                                                    |
| Function / source references                                 |        |                                                   |                                                                                    |
| proposal                                                     |        |                                                   |                                                                                    |
| printit pdfcert.go (QR → explorer.verae.ai/time)             |        |                                                   |                                                                                    |
| itad docs 09 §4                                              |        |                                                   |                                                                                    |
| API id                                                       | Method | Path                                              | Key params (name:type)                                                             |
| v1.timestamp.status                                          | GET    | customer.verae.ai/v1/timestamp/status             | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                 | —      | peergos.verae.ai (Peergos HTTP/API + local rust)  | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                 | POST   | customer.verae.ai/v1/timestamp                    | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-V2 — Verify — mobile (QR scan landing)

Landing page after scanning a certificate QR on a phone; can also check the PDF the user has.




ZP-V5

| Features                     |        |                                                  |                                                                                    |
|------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Verdict card.              |        | • Key facts.                                     |                                                                                    |
| • Compare with local copy.   |        |                                                  |                                                                                    |
| Function / source references |        |                                                  |                                                                                    |
| proposal                     |        |                                                  |                                                                                    |
| API id                       | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status          | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                 | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                 | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

ZP-V3 — Verify — mobile (QR scan landing)

Landing page after scanning a certificate QR on a phone; can also check the PDF the user has.




ZP-V5

| Features                     |        |                                                  |                                                                                    |
|------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Verdict card.              |        | • Key facts.                                     |                                                                                    |
| • Compare with local copy.   |        |                                                  |                                                                                    |
| Function / source references |        |                                                  |                                                                                    |
| proposal                     |        |                                                  |                                                                                    |
| API id                       | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status          | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                 | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                 | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf

ZP-V4 — Verify — not found / tampered / revoked

Negative outcomes explained without blame; certificate mismatch is called out as possible tampering.




ZP-V4

| Features                                                                               |        |                                                               |                                                                                    |
|----------------------------------------------------------------------------------------|--------|---------------------------------------------------------------|------------------------------------------------------------------------------------|
| • Neutral not-found verdict.                                                           |        | • Help: hash sensitivity, compare with the printed multihash. |                                                                                    |
| • Mismatch vs scanned certificate (red). Revoked certificates show reason + successor. |        |                                                               |                                                                                    |
| Function / source references                                                           |        |                                                               |                                                                                    |
| proposal                                                                               |        |                                                               |                                                                                    |
| printit pdfcert.go (QR → explorer.verae.ai/time)                                       |        |                                                               |                                                                                    |
| itad docs 09 §4                                                                        |        |                                                               |                                                                                    |
| API id                                                                                 | Method | Path                                                          | Key params (name:type)                                                             |
| v1.timestamp.status                                                                    | GET    | customer.verae.ai/v1/timestamp/status                         | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                                                                           | —      | peergos.verae.ai (Peergos HTTP/API + local rust)              | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                                                                           | POST   | customer.verae.ai/v1/timestamp                                | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAE-API-REFERENCE.pdf

ZP-V5 — Verify — mobile (QR scan landing)

Landing page after scanning a certificate QR on a phone; can also check the PDF the user has.



ZP-V5

| Features                     |        |                                                  |                                                                                    |
|------------------------------|--------|--------------------------------------------------|------------------------------------------------------------------------------------|
| • Verdict card.              |        | • Key facts.                                     |                                                                                    |
| • Compare with local copy.   |        |                                                  |                                                                                    |
| Function / source references |        |                                                  |                                                                                    |
| proposal                     |        |                                                  |                                                                                    |
| API id                       | Method | Path                                             | Key params (name:type)                                                             |
| v1.timestamp.status          | GET    | customer.verae.ai/v1/timestamp/status            | sha256:string (64 hex), jobId:string?                                              |
| peergos.cube                 | —      | peergos.verae.ai (Peergos HTTP/API + local rust) | username:string, password:string, path:string, bytes:bytes                         |
| v1.timestamp                 | POST   | customer.verae.ai/v1/timestamp                   | sha256:string (64 hex), restamp:boolean, restampOf:string jobId?, metadata:object? |

Sample calls + full param tables → VERAЕ-API-REFERENCE.pdf